

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id 2602939 (S/N 1092) Component

Compressor Fluid KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA013965	KCP29749	
Sample Date		Client Info		16 Mar 2024	14 Dec 2020	
Machine Age	hrs	Client Info		46108	37182	
Oil Age	hrs	Client Info		2754	0	
Oil Changed		Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	<1	
Aluminum	ppm	ASTM D5185m	>10	0	0	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper			>50	1	1	
Tin	ppm	ASTM D5185m	>10	0	0	
	ppm		>10		0	
Antimony Vanadium	ppm	ASTM D5185m				
	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	<1	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	100	29	0	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	0	0	78	
Zinc	ppm	ASTM D5185m	0	19	0	
Sulfur	ppm	ASTM D5185m	23500	20305	7767	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	
Sodium	ppm	ASTM D5185m		19	<1	
Potassium	ppm	ASTM D5185m	>20	0	7	
Water	%	ASTM D6304	>0.05	0.014	0.007	
ppm Water	ppm	ASTM D6304	>500	143	77.3	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		11755		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14µm		ASTM D7647	>80	<u> </u>		
Particles >21µm		ASTM D7647	>20	<u> </u>		
Particles >38µm		ASTM D7647	>4	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	A 21/19/14		
Oli Cleaniness				 _		
FLUID DEGRADA		method	limit/base	current	history1	history2
	TION mg KOH/g	()			history1 0.503	history2

Report Id: GRABRI [WUSCAR] 06130651 (Generated: 03/30/2024 13:23:05) Rev: 1

Page 1



12

.10 1

8

61

4

21

0

12000

1000

800 (maa)

600 Water 400

200

1.20

<u>©</u>0.9 E0.72

204

Poid 0.2

0.00

1000

600 Water (

4000

200

60

ပ္ 5(

-₹3 45

40

35

Ĕ

Der.

Water (KF)

Abnormal

Viscosity @ 40°C

lec]

S 55

Abnorma

S

Dec]

Acid Number

Dec]

Water (KF)

particles (1

Built for a lifetime

______14µm

OIL ANALYSIS REPORT 🔺 Particle Trend VISUAL

