

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

#### Area M-460 [8982] Machine Id KAESER 1222 - AMAZON Component

Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


				Mar2024		
SAMPLE INFORM	ΛΑΤΙΟΝ	method	limit/base	current	history1	history2
Sample Number		Client Info		UDI06130746		
Sample Date		Client Info		19 Mar 2024		
Machine Age	hrs	Client Info		3536		
Oil Age	hrs	Client Info		3536		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	0		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	1		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>50	1		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	90	30		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	100	80		
Calcium	ppm	ASTM D5185m	0	7		
Phosphorus	ppm	ASTM D5185m	0	0		
Zinc	ppm	ASTM D5185m	0	3		
Sulfur	ppm	ASTM D5185m	23500	18347		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		15		
Potassium	ppm	ASTM D5185m	>20	8		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.37		





# **OIL ANALYSIS REPORT**

VISUAL



	VISUAL		method	limit/base	current	nistory i	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Mar19,24	Appearance	scalar	*Visual	NORML	NORML		
Mari	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.05	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPERT	IFS	method	limit/base	e current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	45	44.1		
****							
	SAMPLE IMAGES	3	method	limit/base	e current	history1	history2
Mar19/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Metal	s		Mar19/24			
	Viscosity @ 40°C			Mar19/24	Acid Number		
	60 55 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5			Mar19/24	20 96 72 48 24 24 24 50 6 1 20 6 72 48 24		
Laboratory Sample No. Lab Number Unique Number Test Package iscuss this sample report,	: WearCheck USA - 50 : UDI06130746 : 06130746 : 10950211 : IND 2	Recei Teste Diagn	ved : 27 d : 28 losed : 30	, NC 27513 7 Mar 2024 8 Mar 2024 Mar 2024 - Do	B DELTA II	DOWNE	

Ē

Contact/Location: MICHAEL FERRIS - UCDELDOW