## Sullivan Palatek.

# **OIL ANALYSIS REPORT**

### PALEXTRA 44 Machine Id SULLIVAN PALATEK 20EB000987 - AC1024 Component

Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06130772		
Sample Date		Client Info		20 Mar 2024		
Machine Age	hrs	Client Info		18849		
Oil Age	hrs	Client Info		9597		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	0.3	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	0.3	0		
Magnesium	ppm	ASTM D5185m	0.4	1		
Calcium	ppm	ASTM D5185m	0	3		
Phosphorus	ppm	ASTM D5185m	689	393		
Zinc	ppm	ASTM D5185m	0	0		
Sulfur	ppm	ASTM D5185m	1237	779		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m		30		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.135	0.21		



# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	t history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Mar20/24	Appearance	scalar	*Visual	NORML	NORML			
Ma	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
1	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	IES	method	limit/base	current	t history1	history2	
	Visc @ 40°C	cSt	ASTM D445	44.62	48.5			
	SAMPLE IMAGES	5	method	limit/base	current	t history1	history2	
Mar20/24	Color				-	no image	no image	
	Bottom					no image	no image	
	Non-ferrous Metal	S		Mar2024				
	55T		0.25 (9)0.25 H2y 0.20 U 0.15 4 0.05 9 0.05 9 0.05		Acid Num	ber		
	50 - Abnormal				20			
	(C) 00 45 - Base			Ĕ 0.1	5 - Base			
	40 - Abnormal			e 0.1	10			
			mannannann	Z 0.0	)5 -			
	354				10			
	Mar20/24			Mar20/24	Mar20/24		Mar20/24	
Laboratory	: WearCheck USA - 501 Madison Ave					TRAIL KING INDUSTRIES		
- Denotes test methods that	10950237 Diagnosed : 30 Mar 2024 - Don Baldridge				Ū	MITCHELL, SD US 57301 Contact: DAN ANDERSON DANDERSON@TRAILKING.COM T: GM 106:2012) F:		