

# **OIL ANALYSIS REPORT**

SAMPLE INFORMATION

ISO

# KAESER SK 26 1423386 (S/N 0264717)

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

**DIAGNOSIS** 

## Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a high amount of particulates present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


OAMI LE IMI OTTIV	711011	metriod	IIIIII/Dase	Current	Thistory	HISTOTYZ
Sample Number		Client Info		KCPA015818	KCP28242	
Sample Date		Client Info		19 Mar 2024	26 Apr 2021	
Machine Age	hrs	Client Info		21003	20959	
Oil Age	hrs	Client Info		23	0	
Oil Changed		Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	<1	0	
Silver	ppm	ASTM D5185m	>2	<1	<1	
Aluminum	ppm	ASTM D5185m	>10	2	1	
Lead	ppm	ASTM D5185m	>10	- <1	<1	
Copper	ppm	ASTM D5185m	>50	<1	<1	
Tin	ppm	ASTM D5185m	>10	<1	<1	
Antimony	ppm	ASTM D5185m	7 10		0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		<1	0	
	ррпп			<b>\</b> 1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	10	
Barium	ppm	ASTM D5185m	90	22	52	
Molybdenum	ppm	ASTM D5185m		<1	<1	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m	90	70	76	
Calcium	ppm	ASTM D5185m	2	6	3	
Phosphorus	ppm	ASTM D5185m		<1	<1	
Zinc	ppm	ASTM D5185m		2	1	
Sulfur	ppm	ASTM D5185m		21083	14789	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	
Sodium	ppm	ASTM D5185m		8	14	
Potassium	ppm	ASTM D5185m	>20	2	1	
Water	%	ASTM D6304	>0.05	0.012	0.021	
ppm Water	ppm	ASTM D6304	>500	121	213.2	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		8185	13111	
Particles >6µm		ASTM D7647	>1300	<u>^</u> 2419	<b>4711</b>	
Particles >14µm		ASTM D7647	>80	<b>197</b>	<u> 722</u>	
Particles >21µm		ASTM D7647	>20	<u></u> 53	<u>^</u> 239	
Particles >38µm		ASTM D7647	>4	2	<u> </u>	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 20/18/15	<b>△</b> 19/17	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

0.302



# **OIL ANALYSIS REPORT**

