


OIL ANALYSIS REPORT

Sample Rating Trend



ISO

Machine Id KAESER CSD 100 7683553 (S/N 1035)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2022 Mar2024 Mar2		024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA014966	KCPA014958	KCP42033
Sample Date		Client Info		13 Mar 2024	13 Mar 2024	11 Mar 2022
Machine Age	hrs	Client Info		10486	10486	2191
Oil Age	hrs	Client Info		0	0	2191
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1	0	1
Chromium	ppm	ASTM D5185m	>10	<1	<1	0
Nickel	ppm	ASTM D5185m	>3	<1	<1	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	<1
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	3	6	2
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	0	4	0
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	100	26	40	67
Calcium	ppm	ASTM D5185m	0	4	0	1
Phosphorus	ppm	ASTM D5185m	0	1	0	6
Zinc	ppm	ASTM D5185m	0	14	6	6
Sulfur	ppm	ASTM D5185m	23500	25570	25303	15578
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	1	<1
Sodium	ppm	ASTM D5185m		5	13	14
Potassium	ppm	ASTM D5185m	>20	1	2	4
Water	%	ASTM D6304	>0.05	0.006	0.013	0.016
ppm Water	ppm	ASTM D6304	>500	60	130	169.8
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		7773	20884	6887
Particles >6µm		ASTM D7647	>1300	2789	<u></u> 6566	512
Particles >14µm		ASTM D7647	>80	335	△ 673	24
Particles >21µm		ASTM D7647	>20	<u> </u>	<u>^</u> 203	7
Particles >38µm		ASTM D7647	>4	<u>^</u> 6	<u>8</u>	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	20/19/16	22/20/17	16/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045	1.0	0.40	0.42	0.40

Acid Number (AN)

mg KOH/g ASTM D8045 1.0

0.42

0.40

0.40



OIL ANALYSIS REPORT

