




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
MCI 2037

Component
Diesel Engine

Fluid
PURUS 10W30 BLEND (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0859026	WC0859050	---
Sample Date	Client Info			29 Feb 2024	27 Sep 2023	---
Machine Age	mls	Client Info		473707	427723	---
Oil Age	mls	Client Info		21000	0	---
Oil Changed	Client Info			Changed	N/A	---
Sample Status				NORMAL	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<1.0	0.4	---
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	16	34	---
Chromium	ppm	ASTM D5185m	>20	2	4	---
Nickel	ppm	ASTM D5185m	>2	1	0	---
Titanium	ppm	ASTM D5185m	>2	<1	<1	---
Silver	ppm	ASTM D5185m	>2	0	0	---
Aluminum	ppm	ASTM D5185m	>20	4	7	---
Lead	ppm	ASTM D5185m	>40	0	0	---
Copper	ppm	ASTM D5185m	>330	<1	<1	---
Tin	ppm	ASTM D5185m	>15	<1	0	---
Vanadium	ppm	ASTM D5185m		<1	0	---
Cadmium	ppm	ASTM D5185m		0	0	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		20	18	---
Barium	ppm	ASTM D5185m		0	0	---
Molybdenum	ppm	ASTM D5185m		63	77	---
Manganese	ppm	ASTM D5185m		<1	0	---
Magnesium	ppm	ASTM D5185m		907	1039	---
Calcium	ppm	ASTM D5185m		1088	1225	---
Phosphorus	ppm	ASTM D5185m		980	1218	---
Zinc	ppm	ASTM D5185m		1220	1355	---
Sulfur	ppm	ASTM D5185m		3663	3653	---



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6	8	---
Sodium	ppm	ASTM D5185m		2	<1	---
Potassium	ppm	ASTM D5185m	>20	2	1	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	1.1	1	---
Nitration	Abs/cm	*ASTM D7624	>20	9.3	9.6	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.6	21.8	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.0	17.8	---
Base Number (BN)	mg KOH/g	ASTM D2896		8.2	9.4	---







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.5	12.3	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0859026 **Received** : 28 Mar 2024
Lab Number : 06131640 **Tested** : 28 Mar 2024
Unique Number : 10951105 **Diagnosed** : 02 Apr 2024 - Don Baldrige
Test Package : FLEET

JEFFERSON LINES
 1830 4TH AVE N
 BILLINGS, MT
 US 59101
 Contact: BILLINGS SHOP
 billingsshop@jeffersonlines.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: