


OIL ANALYSIS REPORT







Recommendation

Contamination

Fluid Condition

suitable for further service.

Wear

oil.

after fluid and filter change.)

All component wear rates are normal.

Resample at the next service interval to monitor. (Customer Sample Comment: 200 hour oil sample

There is no indication of any contamination in the

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is

Grand Blanc CAT 1 GBLM01BE


Biogas Engine


CHEVRON HDAX 9500 GAS ENGINE OIL 40 (--- GAL)


SENGINE OIL 40 (,	12023 Mar20	23 WINY2023 JUN2023	-		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0905742	WC0905728	WC0905676
Sample Date		Client Info		25 Mar 2024	19 Mar 2024	23 Feb 2024
Machine Age	hrs	Client Info		7471	7276	84933
Oil Age	hrs	Client Info		212	130	390
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>.11	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>15	<1	6	7
Chromium	ppm	ASTM D5185m	>4	0	<1	<1
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>6	1	3	2
Lead	ppm	ASTM D5185m	>9	0	<1	<1
Copper	ppm	ASTM D5185m	>6	1	8	2
Tin	ppm	ASTM D5185m	>4	0	2	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		8	2	6
Barium	ppm	ASTM D5185m		0	1	0
Molybdenum	ppm	ASTM D5185m		2	2	3
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		9	8	22
Calcium	ppm					
	pp	ASTM D5185m		1508	1609	1953
Phosphorus	ppm	ASTM D5185m ASTM D5185m		1508 224	1609 241	1953 293
Zinc	ppm	ASTM D5185m		224	241	293
Zinc	ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base	224 275	241 308	293 361 2921
Zinc Sulfur	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	224 275 2219	241 308 2641	293 361 2921
Zinc Sulfur CONTAMINANTS	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method		224 275 2219 current	241 308 2641 history1	293 361 2921 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	>181	224 275 2219 current 30	241 308 2641 history1 62	293 361 2921 history2 96
Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm S ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D5185m ASTM D5185m	>181 >21	224 275 2219 current 30 2	241 308 2641 history1 62 <1	293 361 2921 history2 96 4 0
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm S ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	>181 >21 >20	224 275 2219 current 30 2 0	241 308 2641 history1 62 <1 3	293 361 2921 history2 96 4 0
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm S ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m Method	>181 >21 >20	224 275 2219 current 30 2 0 current	241 308 2641 history1 62 <1 3 history1	293 361 2921 history2 96 4 0 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm S ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844	>181 >21 >20	224 275 2219 current 30 2 0 0 current 0	241 308 2641 history1 62 <1 3 history1 0	293 361 2921 history2 96 4 0 history2 0.1
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	>181 >21 >20	224 275 2219 current 30 2 0 current 0 4.9	241 308 2641 62 <1 3 history1 0 4.6	293 361 2921 history2 96 4 0 history2 0.1 6.2 23.3
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844 *ASTM D7844	>181 >21 >20 limit/base	224 275 2219 current 30 2 0 current 0 4.9 15.9	241 308 2641 <u>history1</u> 62 <1 3 <u>history1</u> 0 4.6 16.6	293 361 2921 history2 96 4 0 history2 0.1 6.2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRAD/	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7844 *ASTM D7844 *ASTM D7624	>181 >21 >20 limit/base	224 275 2219 current 30 2 0 current 0 4.9 15.9 current	241 308 2641 62 <1 3 history1 0 4.6 16.6 history1	293 361 2921 history2 96 4 0 history2 0.1 6.2 23.3 history2




OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.11	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT		method	limit/base	ourropt	history1	history?
FLUID PROPER I	IES	methoa	Innivbase	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	13.4	13.1	13.3	13.6










10

Feb6/23 Mar20/23




Chromium (ppm)





6 Bas (mg KOH/g Base 0.0 May3/23 Jun7/23 Aug 14/23 0ct5/23 Dec4/23 eh6/73 Mar20/23 an30/24



Aug 14/23

0ct5/23 Dec4/23

Jan30/24

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

May3/23

hun7/73