

## **OIL ANALYSIS REPORT**

#### Sample Rating Trend



#### Area ENGINE ROOM Machine Id AC-3

Component Air Compressor Fluid

### SULLAIR SULLUBE (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the fluid.


#### Fluid Condition

The condition of the fluid is acceptable for the time in service.

		Jul2020	Jul2023	Aug2023 Oct2023	Mar2024	
SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0903607	WC0857519	WC0838501
Sample Date		Client Info		17 Mar 2024	15 Oct 2023	08 Aug 2023
Machine Age	hrs	Client Info		0	0	60525
Oil Age	hrs	Client Info		0	0	60525
Oil Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1	1	2
Chromium	ppm	ASTM D5185m	>4	0	3	0
Nickel	ppm	ASTM D5185m	>4	<1	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	<1
Lead	• •	ASTM D5185m	>20	0	0	0
Copper	ppm ppm	ASTM D5185m	>20	4	11	7
Tin	ppm	ASTM D5185m	>5	1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	0	<1
Barium	ppm	ASTM D5185m	745	734	818	642
Molybdenum	ppm	ASTM D5185m	0.0	0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	0.0	2	<1	<1
Calcium	ppm	ASTM D5185m	1	4	11	7
Phosphorus	ppm	ASTM D5185m	3	0	0	6
Zinc	ppm	ASTM D5185m	0.1	80	296	129
Sulfur	ppm	ASTM D5185m	240	399	508	337
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	2
Sodium	ppm	ASTM D5185m		39	93	56
Potassium	ppm	ASTM D5185m	>20	5	9	6
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.6	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
:18:01) Rev: 1					Submitted By: B	
,						



# **OIL ANALYSIS REPORT**



			ethod lin			ory1 history2
And a second	Visc @ 40°C	cSt AST	M D445 38.	1 <b>41.6</b>	43.8	41.2
	SAMPLE IMAGE	ES m	ethod lin	nit/base cur	rent histo	ory1 history2
	Color					no image
Mar17/24	Bottom					no image
	GRAPHS					
	Ferrous Alloys					
	Non-ferrous Met		23 0ct15/23 0ct15/23	- ] ] ] ]		
	Viscosity @ 40°C	Augeiza	Oct15/23 Oct15/24			
	36 - Abnormal					
	32	Aug8/23 +	0ct15/23 +	-		
	: WearCheck USA - 5 : WC0903607 : 06132566 : 10952031 : IND 1	01 Madison Av Received Tested Diagnose	: 28 Mar : 01 Apr	<sup>·</sup> 2024		O FOODS-GREELI 1302 1ST A GREELEY, C US 80631-59 Contact: ERIC KLI

Test Certificate L2367 To discuss this samp \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (970)347-5190