

OIL ANALYSIS REPORT

NORMAL

FRICK 4 (S/N SGC19180785)

Refrigeration Compressor

USPI 1009-68 SC (40 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


							1003000000
							1001000000
							1111111
							T T T T T T T
							1101101010
							1
		11111	1.1.1.1.1.1				L L S L L L L
		1 S. C. C.	1.1.1.1.1				
	1.1.1.1.1			11111			
h	Jul2015	0ct2016	Jan2018	Apr2019	Jul2020	Sep2021	Mar2023





SAMPLE INFORM	IATION	method				history2
Sample Number		Client Info		USP0008246	USP0004530	USP232110
Sample Date		Client Info		26 Mar 2024	26 Dec 2023	28 Sep 2023
Machine Age	hrs	Client Info		73290	73033	72287
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	0	0	0
Chromium	ppm	ASTM D5185m		<1	0	0
Nickel	ppm	ASTM D5185m	~ _	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum		ASTM D5185m		0 <1	0	0
Lead	ppm	ASTM D5185m	>2	0	0	0
	ppm			0		<1
Copper	ppm	ASTM D5185m	>8		0	
Tin	ppm	ASTM D5185m	>4	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		U	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		0	0	0
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m	50	0	0	14
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	1
Sodium	ppm	ASTM D5185m		<1	0	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.01	0.001	0.005	0.006
ppm Water	ppm	ASTM D6304	>100	0	56	61.6
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	777	387	433
Particles >6µm		ASTM D7647	>2500	227	110	151
Particles >14µm		ASTM D7647	>320	23	11	14
Particles >21µm		ASTM D7647	>80	6	2	4
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	17/15/12	16/14/11	16/14/11
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974	0.005	0.027	0.014	0.014



OIL ANALYSIS REPORT








0

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	67	65.1	64.5	64.6
SAMPLE IMAGES	\$	method				history2
Color				•	e mann	
Bottom				(\bigcirc)	(\circ)	(\bigcirc)



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

C/LC/na

Certificate L2367

Page 2 of 2

F: