

## **OIL ANALYSIS REPORT**

### Area S-46 [282752] **ATLAS COPCO AII474270 - ENGAGE TECH** Component Compressor

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sample Rating Trend								
	Mar2024							




NORMAL

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0000674		
Sample Date		Client Info		20 Mar 2024		
Machine Age	hrs	Client Info		10986		
Oil Age	hrs	Client Info		200		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>5	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	0		
Copper	ppm	ASTM D5185m	>65	0		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		188		
Zinc	ppm	ASTM D5185m		4		
Sulfur	ppm	ASTM D5185m		417		
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.10		



# **OIL ANALYSIS REPORT**

VISUAL



White Metal Yellow Metal Precipitate Silt Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAG Color Bottom GRAPHS Ferrous Alloys	cSt	*Visual *Visual *Visual *Visual *Visual *Visual *Visual *Visual <b>method</b> ASTM D445 <b>method</b>	NONE NONE NONE NONE NONE NONE NORML NORML >0.1 Imit/base Imit/base	NONE NONE NONE NONE NONE NORML NORML NORML A3.8 Current	history1  no image	       history2 history2 no image
Precipitate Silt Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual *Visual *Visual <b>method</b> ASTM D445	NONE NONE NONE NORML NORML >0.1	NONE NONE NONE NORML NORML NEG NEG Current 43.8	    history1 history1 no image	    history2 history2
Silt Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAG Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual *Visual *Visual <b>method</b> ASTM D445	NONE NONE NORML NORML >0.1 limit/base	NONE NONE NORML NORML NEG NEG Current 43.8	history1 no image	    history2 history2
Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAG Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual <b>method</b> ASTM D445	NONE NORML NORML >0.1	NONE NORML NORML NEG NEG current 43.8	   history1  history1	   history2  history2
Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual method ASTM D445	NONE NORML NORML >0.1	NONE NORML NORML NEG NEG current 43.8	   history1  history1 no image	   history2  history2
Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual method ASTM D445	NORML >0.1 limit/base	NORML NORML NEG NEG current 43.8	  history1  history1 no image	  history2  history2 no image
Appearance Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar scalar scalar scalar scalar scalar	*Visual *Visual *Visual method ASTM D445	NORML >0.1 limit/base	NORML NORML NEG NEG current 43.8	 history1  history1 no image	 history2  history2 no image
Odor Emulsified Water Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar RTIES cSt	*Visual *Visual method ASTM D445	NORML >0.1 limit/base	NEG NEG current 43.8	 history1  history1 no image	 history2  history2 no image
Free Water FLUID PROPEF Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	scalar scalar RTIES cSt	*Visual *Visual method ASTM D445	>0.1 limit/base	NEG NEG current 43.8	 history1  history1 no image	history2  history2 no image
FLUID PROPER Visc @ 40°C SAMPLE IMAG Color Bottom GRAPHS Ferrous Alloys	RTIES cSt	*Visual method ASTM D445	limit/base	NEG current 43.8	history1  history1 no image	history2  history2 no image
Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	RTIES cSt	method ASTM D445		current 43.8	history1	history2
Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	cSt	ASTM D445		43.8	history1	history2
SAMPLE IMAGE			limit/base		history1 no image	no image
Color Bottom GRAPHS Ferrous Alloys	ES	method	limit/base	current	no image	no image
Bottom GRAPHS Ferrous Alloys						
GRAPHS Ferrous Alloys					no image	no image
Ferrous Alloys						
Non-ferrous Met			Mar20/24 Mar20/24			
55 50 25 45 40 40 40 40 40			0.00			
: WearCheck USA - 5 : UFD0000674 : 06133532	Recei Teste	ived : 29 ed : 01	7, NC 27513 9 Mar 2024 1 Apr 2024	FL	14250 JL	NAMICS - (MN JDICIAL ROAI RNSVILLE, MI US 5530
	Biagi				Contact: Se	ervice Manage
	55 50 40 40 40 40 40 40 40 40 40 4	: WearCheck USA - 501 Madiso : UFD0000674 Rece : 06133532 Teste : 10952997 Diagr	55 60 60 60 60 60 60 60 60 60 60	55 50 50 50 45 40 40 40 40 40 40 40 40 40 40	<ul> <li>WearCheck USA - 501 Madison Ave., Cary, NC 27513</li> <li>UFD0000674</li> <li>Beceived : 29 Mar 2024</li> <li>: 06133532</li> <li>Tested : 01 Apr 2024</li> </ul>	State     Number       50     45       4

Contact/Location: Service Manager - UCFLUBUR Page 2 of 2