

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

JSF TCCEAU7204 (S/N TCEAU7204)

Hydraulic System

ANDEROL ROYCO 500 (30 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target cleanliness. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. Counts X100.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


				Mar2024		
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0862382		
Sample Date		Client Info		28 Mar 2024		
Machine Age	mls	Client Info		0		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>20	1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	<1		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m		0		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m	220	0		
Cadmium	ppm	ASTM D5185m		0		
	ppin			-		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Vanganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		995		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	563		
Particles >6µm		ASTM D7647	>1300	121		
Particles >14µm		ASTM D7647	>160	15		
Particles >21µm		ASTM D7647	>40	6		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	16/14/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.06	0.23		
25:55) Dov: 1			0.00			


Report Id: EATBET [WUSCAR] 06133778 (Generated: 03/29/2024 15:35:55) Rev: 1

Contact/Location: REINALDO CASTILLA - EATBET



OIL ANALYSIS REPORT





NONE *Visual NONE White Metal scalar Yellow Metal *Visual NONE NONE scalar NONE Precipitate scalar *Visual NONE scalar *Visual NONE NONE Debris *Visual NONE scalar NONE Sand/Dirt NONE NONE scalar *Visual NORML Appearance scalar *Visual NORML Odor *Visual NORML NORML scalar **Emulsified Water** scalar *Visual >0.05 NEG Free Water scalar *Visual NEG FLUID PROPERTIES Visc @ 40°C cSt ASTM D445 25.4 25.13 SAMPLE IMAGES Color no image no image Bottom no image no image GRAPHS Ferrous Alloys Particle Count 491,52 122,88 mac 30.72 7.68 (per 1 ml Mar28/24 4406 1.920 :1999 Cle Non-ferrous Metals 480 120 14 maa 30 Mar28/2 21µ 38µ Viscosity @ 40°C Acid Number 30 (^{0.25}) (⁰/HO) 28 () 26 Ê 0.15 zz 24 - ² 0.10 Base 22 Acid Nu 0.05 20 0.00 Mar28/24 Aar28 EATON AEROSPACE LLC Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC0862382 15 DURANT AVE Received : 29 Mar 2024 Lab Number : 06133778 BETHEL, CT Tested : 29 Mar 2024 Unique Number : 10953243 : 29 Mar 2024 - Doug Bogart US 06801 Diagnosed Test Package : IND 2 Contact: REINALDO CASTILLA To discuss this sample report, contact Customer Service at 1-800-237-1369. reinaldocastilla@eaton.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (203)240-2520 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:

Certificate L2367