

## **OIL ANALYSIS REPO**

SAMPLE INFORM

Sample Number

Sample Date

Machine Age

Oil Changed

Sample Status

CONTAMINATION

Oil Age

Water

Iron

Nickel

Titanium Silver Aluminum Lead Copper Tin Vanadium

Cadmium

Chromium

### Area [1150] BALEMASTER 52100G-10 15403 - TJ MAXX WORCES Component

**Hydraulic System** 

AW HYDRAULIC OIL ISO 46 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

RT	Samp	le Rating Tre	nd	N	NORMAL		
STER		Feb2023	Mar2024				
ΛΑΤΙΟΝ	method	limit/base	current	history1	history2		
hrs hrs	Client Info Client Info Client Info Client Info Client Info		WC0885306 24 Mar 2024 0 0 Filtered NORMAL	WC0749831 04 Feb 2023 0 0 Filtered NORMAL	   		
N	method	limit/base	current	history1	history2		
	WC Method	>0.05	NEG	NEG			
	method	limit/base	current	history1	history2		
ppm ppm	ASTM D5185m ASTM D5185m	>20 >20	<1 0	1 0			
ppm	ASTM D5185m	>20	0	0			
ppm	ASTM D5185m		0	0			
ppm ppm	ASTM D5185m ASTM D5185m	>20	0	0			
ppm	ASTM D5185m	>20	0	<1			
ppm	ASTM D5185m	>20	<1	<1			
ppm	ASTM D5185m	>20	0	0			
ppm	ASTM D5185m		0	0			
ppm	ASTM D5185m		0	0			

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	<1	2	
Barium	ppm	ASTM D5185m	5	0	0	
Molybdenum	ppm	ASTM D5185m	5	0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	25	10	15	
Calcium	ppm	ASTM D5185m	200	89	87	
Phosphorus	ppm	ASTM D5185m	300	287	287	
Zinc	ppm	ASTM D5185m	370	354	363	
Sulfur	ppm	ASTM D5185m	2500	3752	3866	

CONTAMINANTS	;	method				history2
Silicon	ppm	ASTM D5185m	>15	0	<1	
Sodium	ppm	ASTM D5185m		<1	<1	
Potassium	ppm	ASTM D5185m	>20	0	<1	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		998	5674	
Particles >6µm		ASTM D7647	>5000	293	1542	
Particles >14µm		ASTM D7647	>640	33	88	
Particles >21µm		ASTM D7647	>160	10	17	

Particles >21µm		ASTM D7647	>160	10	17	
Particles >38µm		ASTM D7647	>40	0	0	
Particles >71µm		ASTM D7647	>10	0	0	
Oil Cleanliness		ISO 4406 (c)	>/19/16	17/15/12	20/18/14	
FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	0.31	0.46	

Acid Number (AN) mg KOH/g ASTM D8045 0.57


Contact/Location: JEFF BURNLEY - ADVFRA


Report Id: ADVFRA [WUSCAR] 06133987 (Generated: 04/01/2024 20:55:18) Rev: 1


Page 1 of 2



# **OIL ANALYSIS REPORT**







	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
*****************************	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Mar24/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Mar	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	44.5	43.0	
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Mar24/24	Color						no image
	Bottom						no image
	GRAPHS						
	Ferrous Alloys			90.000 A 2010	Particle Count		1945
	<sup>10</sup> iron			491,520			T <sup>2</sup>
	6			122,880			-2
640				30,720			
N.A.	2-			50,720			+2
	0			7,680			-2
	Feb 4/23			Mar24/24. (per 1 ml)			
	뀰			s (per )			***
	Non-ferrous Metal	s					-2
	10 copper			Mar24/24 Mar24/24 1500 1500 1500 1500 1500 1500 1500 150			
	0 assessesses lead						1
	E 6 - tin			30	-		-1
	2			8			-1
V CI V CI		a			<b>Sereve</b> mal	/	
- M	Feb 4/23			Mar24/24			8
	9 <u>-</u>			Mar2		,	
	Viscosity @ 40°C			4	ونام Acid Number	14μ 21μ	38µ 71µ
	<sup>55</sup>			<u>,</u> 1.00			
	50 Abnormal			0.80 K			
	() 아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아아			(B) 100- (B)	Base		
				e 0.40			
	40			8 0.20	Abnormal		
	354			0.00			
	Feb 4/23			Mar24/24	Feb 4/23		
		1 Madiso	n Ave., Cary	r, NC 27513 Mar 2024	ADV		MENT SAL

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: JEFF BURNLEY - ADVFRA

F: (215)723-7201