


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

GARDNER DENVER S291136 - TNT TRUCK

Compressor

QUINCY QUINSYN (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Feb 202	3 Aug ² 023	Nov2023 Fr	ab2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO50002114	QUC0000477	QUC0000585
Sample Date		Client Info		20 Feb 2024	16 Nov 2023	15 Aug 2023
Machine Age	hrs	Client Info		21161	21147	21146
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	7	6	8
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	6	6	4
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	<1	<1	0
Tin	ppm	ASTM D5185m	>15	0	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		0	2	2
Calcium	ppm	ASTM D5185m		6	2	9
Phosphorus	ppm	ASTM D5185m		109	120	0
Zinc	ppm	ASTM D5185m		29	41	17
Sulfur	ppm	ASTM D5185m		1340	1224	1420
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	3	4
Sodium	ppm	ASTM D5185m		5	3	4
Potassium	ppm	ASTM D5185m	>20	<1	2	0
Water	%	ASTM D6304	>0.1	0.012	0.049	0.006
ppm Water	ppm	ASTM D6304	>1000	121	490	67.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<u> </u>	<u> </u> 72257	△ 91987
Particles >6µm		ASTM D7647	>2500	44333	3010	<u>▲</u> 15266
Particles >14μm		ASTM D7647	>320	3920	16	441
Particles >21µm		ASTM D7647	>80	<u> </u>	4	<u>\$\infty\$ 95</u>
Particles >38μm		ASTM D7647	>20	<u> </u>	1	3
Particles >71μm		ASTM D7647	>4	1	1	1
Oil Cleanliness		ISO 4406 (c)	>20/18/15	<u>4</u> 24/23/19	<u>\$\text{\Delta}\$ 23/19/11</u>	<u>4</u> 24/21/16
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	.10	0.35	0.30	0.31



OIL ANALYSIS REPORT

