

OIL ANALYSIS REPORT

Area [21688] 80-241

Hydraulic System

ConocoPhillips power tran oil (--- GAL)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: ConocoPhillips powertran)

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			May2022	Mar2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0836091	WC0549107	
Sample Date		Client Info		20 Mar 2024	19 May 2022	
Machine Age	hrs	Client Info		1754	1132	
Oil Age	hrs	Client Info		622	1132	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	3	3	
Chromium	ppm	ASTM D5185m	>10	<1	1	
Nickel	ppm	ASTM D5185m	>10	0	0	
Titanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m		0	<1	
Aluminum	ppm	ASTM D5185m	>10	<1	1	
Lead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m	>75	3	3	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		3	2	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		104	119	
Barium	ppm	ASTM D5185m		<1	0	
Molybdenum	ppm	ASTM D5185m		<1	<1	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m		18	19	
Calcium	ppm	ASTM D5185m		3113	3386	
Phosphorus	ppm	ASTM D5185m		1049	1087	
Zinc	ppm	ASTM D5185m		1329	1375	
Sulfur	ppm	ASTM D5185m		6653	7665	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	13	10	
Sodium	ppm	ASTM D5185m		8	8	
Potassium	ppm	ASTM D5185m	>20	<1	0	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	3756	1930	
Particles >6µm		ASTM D7647	>1300	111	90	
Particles >14μm		ASTM D7647	>160	11	14	
Particles >21µm		ASTM D7647	>40	1	3	
Particles >38μm		ASTM D7647	>10	0	0	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>19/17/14	19/14/11	18/14/11	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

1.46



OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No.

: WC0836091 Lab Number : 06134817 Unique Number: 10954282

Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received **Tested**

: 03 Apr 2024 : 03 Apr 2024 - Don Baldridge Diagnosed

: 01 Apr 2024

5601 S 122ND E AVE TULSA, OK

US 74146 Contact: BEN CALDWELL kevin.marson@wearcheck.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (918)728-5749