

### **OIL ANALYSIS REPORT**

Sample Rating Trend

ISO

# BLOW MOLD 8 (S/N 350R2-3514)

Hydraulic System Fluid MOBIL HYDRAULIC OIL AW 68 (--- GAL)

#### DIAGNOSIS

#### Recommendation

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				-		
			Apr2019	Mar2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0908970	WC0341328	
Sample Date		Client Info		10 Mar 2024	22 Apr 2019	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				ATTENTION	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>20	0	6	
Chromium	ppm	ASTM D5185m	>20	0	<1	
Nickel	ppm	ASTM D5185m	>20	<1	1	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>20	0	0	
Lead	ppm	ASTM D5185m	>20	0	0	
Copper	ppm	ASTM D5185m	>20	<1	<1	
Tin	ppm	ASTM D5185m	>20	0	0	
Antimony	ppm	ASTM D5185m			0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	
Barium	ppm	ASTM D5185m		0	0	
Volybdenum	ppm	ASTM D5185m		0	<1	
Vanganese	ppm	ASTM D5185m		0	<1	
Vagnesium	ppm	ASTM D5185m		<1	0	
Calcium	ppm	ASTM D5185m		81	89	
Phosphorus	ppm	ASTM D5185m		363	263	
Zinc	ppm	ASTM D5185m		456	320	
Sulfur	ppm	ASTM D5185m		1249	6620	
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	0	
Sodium	ppm	ASTM D5185m		<1	0	
Potassium	ppm	ASTM D5185m	>20	2	0	
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	<b>e</b> 8738	1081	
Particles >6µm		ASTM D7647	>1300	1120	152	
Particles >14µm		ASTM D7647	>160	54	13	
Particles >21µm		ASTM D7647	>40	13	2	
Particles >38µm		ASTM D7647	>10	1	0	
Particles >71µm		ASTM D7647	>3	0	0	

ISO 4406 (c) >19/17/14 **20/17/13** 

**Oil Cleanliness** 

17/14/11



## **OIL ANALYSIS REPORT**

Particle Trend	FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
4μm	Acid Number (AN)	mg KOH/g	ASTM D8045		0.36	0.274	
8k disk disk disk disk disk disk disk dis	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	VLITE	
2k	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
s Apr22/19 -	Silt	scalar	*Visual	NONE	NONE	NONE	
Aprž Mari	Debris	scalar	*Visual	NONE	NONE	NONE	
Particle Trend	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
10k	Appearance	scalar	*Visual	NORML	NORML	NORML	
8k - 14μm	Odor	scalar	*Visual	NORML	NORML	NORML	
8k Image: Stress Stre	Emulsified Water Free Water	scalar	*Visual *Visual	>0.05	NEG NEG	NEG	
Abnormal 4k		scalar				NEG	
2k	FLUID PROPER		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	68	64.0	62.7	
Apr22/19 Mar10/24	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Acid Number	Color						no image
1.30 1.25 1.20 1.15 1.10	Bottom						no image
Viscosity @ 40°C	Non-ferrous Meta	s		1,1,220 1,1,220 1,1,220 1,1,220 1,200 1	Severe Acid Numbe	14μ 21μ Γ	-24 -22 -20 -18 -16 -14 -12 -10 -8 -6 $-71\mu$
Certificate 12367 Test Package To discuss this sample report * - Denotes test methods tha	t, contact Customer Serv	Recei Teste Diagr ice at 1-8 7025 sco	ved     : 01       d     : 02       iosed     : 02       00-237-1369       pe of accred	Apr 2024 2 Apr 2024 2 Apr 2024 - W 9. <i>litation</i> .	'es Davis c	Contact: CHUCK huck.calderone@ T:	V DIGGINS S HARVARD, I US 6003 CALDERON

Contact/Location: CHUCK CALDERONE - CONHARIL