


OIL ANALYSIS REPORT

KAESER **KAESER 2961-8972914 - MALNOVE**

Component Compressor



Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06135105		
Sample Date		Client Info		21 Mar 2024		
Machine Age	hrs	Client Info		4006		
Oil Age	hrs	Client Info		1993		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>3	<1		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>10	<1		
Copper	ppm	ASTM D5185m	>50	4		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		6		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		33		
Calcium	ppm	ASTM D5185m		2		
Phosphorus	ppm	ASTM D5185m		9		
Zinc	ppm	ASTM D5185m		6		
Sulfur	ppm	ASTM D5185m		21692		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1		
Sodium	ppm	ASTM D5185m		8		
Potassium	ppm	ASTM D5185m	>20	3		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
A	1/01::	4.0T1.4.D.0.0.:-				

Acid Number (AN) mg KOH/g ASTM D8045

0.36

Sullivan


OIL ANALYSIS REPORT




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.05	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	IFS	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	mmbasc	44.33	Thistory I	motoryz
VISC @ 40 C	USI	ASTIVI D443		44.33		
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image


GRAPHS

Bottom









no image

no image





Certificate 12367

Laboratory

Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 **Sample No.** : UCS06135105 Lab Number : 06135105

Unique Number : 10954570

Received : 01 Apr 2024 Tested Diagnosed

: 05 Apr 2024 : 08 Apr 2024 - Jonathan Hester **RASMUSSEN AIR & GAS ENERGY** 655 240TH STREET

WATERLOO, NE US 68069

Contact: CHASE SVOBODA chase.svoboda@rage-energy.com T: (402)614-9926

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)