




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
SCHTRUCK
 Machine Id
6503 [SCHTRUCK]

Component
Front Center Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (10 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	SBP0007018	SBP0006005	---
Sample Date	Client Info	29 Mar 2024	21 Nov 2023	---
Machine Age	hrs Client Info	74860	36813	---
Oil Age	hrs Client Info	38047	36813	---
Oil Changed	Client Info	Changed	Changed	---
Sample Status		NORMAL	ABNORMAL	---

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	0.0	---
Water	WC Method >0.2	NEG	NEG	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >65	52	108	---
Chromium	ppm ASTM D5185m >5	2	6	---
Nickel	ppm ASTM D5185m >3	0	2	---
Titanium	ppm ASTM D5185m >5	0	<1	---
Silver	ppm ASTM D5185m >2	0	<1	---
Aluminum	ppm ASTM D5185m >35	37	76	---
Lead	ppm ASTM D5185m >10	0	<1	---
Copper	ppm ASTM D5185m >180	38	254	---
Tin	ppm ASTM D5185m >8	<1	4	---
Vanadium	ppm ASTM D5185m	0	<1	---
Cadmium	ppm ASTM D5185m	0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	2	37	---
Barium	ppm ASTM D5185m 0	0	0	---
Molybdenum	ppm ASTM D5185m 60	55	45	---
Manganese	ppm ASTM D5185m 0	<1	5	---
Magnesium	ppm ASTM D5185m 1010	926	551	---
Calcium	ppm ASTM D5185m 1070	1242	1745	---
Phosphorus	ppm ASTM D5185m 1150	905	765	---
Zinc	ppm ASTM D5185m 1270	1156	930	---
Sulfur	ppm ASTM D5185m 2060	2400	1878	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >15	5	10	---
Sodium	ppm ASTM D5185m	4	9	---
Potassium	ppm ASTM D5185m >20	80	172	---

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.7	0.6	---
Nitration	Abs/cm *ASTM D7624 >20	10.1	11.5	---
Sulfation	Abs/.1mm *ASTM D7415 >30	21.9	23.9	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	21.1	28.1	---
Base Number (BN)	mg KOH/g ASTM D2896 9.8	6.3	6.4	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---
Free Water	scalar	*Visual		NEG	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	10.3	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0007018 **Received** : 01 Apr 2024
Lab Number : **06135548** **Tested** : 02 Apr 2024
Unique Number : 10955013 **Diagnosed** : 02 Apr 2024 - Wes Davis
Test Package : FLEET

SCHMIDT TRANSPORTATION - 605449
 108 E Bay Road
 Plattsmouth, NE
 US 68048
 Contact: CASEY WILKIE
 casey@liquidtrucking.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: