

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER SFC 37T 7433567 (S/N 1005)

Component Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		KCPA014801	KCP47204D	KCP43360		
Sample Date		Client Info		20 Mar 2024	07 Feb 2023	29 Dec 2021		
Machine Age	hrs	Client Info		24508	16293	7196		
Oil Age	hrs	Client Info		8215	0	7196		
Oil Changed		Client Info		Changed	Changed	Changed		
Sample Status				NORMAL	NORMAL	ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>50	<1	0	<1		
Chromium	ppm	ASTM D5185m	>10	<1	0	0		
Nickel	ppm	ASTM D5185m	>3	<1	0	0		
Titanium	ppm	ASTM D5185m	>3	<1	0	0		
Silver	ppm	ASTM D5185m	>2	0	0	0		
Aluminum	ppm	ASTM D5185m	>10	2	<1	<1		
Lead	ppm	ASTM D5185m	>10	<1	0	0		
Copper	ppm	ASTM D5185m	>50	11	8	18		
Tin	ppm	ASTM D5185m	>10	1	0	<1		
Antimony	ppm	ASTM D5185m				0		
Vanadium	ppm	ASTM D5185m		<1	0	0		
Cadmium	ppm	ASTM D5185m		<1	0	0		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m	0	0	0	0		
Barium	ppm	ASTM D5185m	90	0	0	0		
Volybdenum	ppm	ASTM D5185m	0	1	0	0		
Manganese	ppm	ASTM D5185m		<1	<1	<1		
Magnesium	ppm	ASTM D5185m	100	5	<1	11		
Calcium	ppm	ASTM D5185m	0	3	0	0		
Phosphorus	ppm	ASTM D5185m	0	<1	8	5		
Zinc	ppm	ASTM D5185m	0	22	6	44		
Sulfur	ppm	ASTM D5185m	23500	21518	21913	17529		
CONTAMINANTS		method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1		
Sodium	ppm	ASTM D5185m		0	<1	15		
Potassium	ppm	ASTM D5185m	>20	2	<1	10		
Water	%	ASTM D6304		0.011	0.007	0.008		
ppm Water	ppm	ASTM D6304		117	73.2	82.4		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2		
Particles >4µm		ASTM D7647		4199	3708	59821		
Particles >6µm		ASTM D7647	>1300	970	345	▲ 25052		
Particles >14µm		ASTM D7647	>80	68	4	🔺 2457		
Particles >21µm		ASTM D7647	>20	17	1	A 383		
Particles >38µm		ASTM D7647	>4	1	0	4		
Particles >71µm		ASTM D7647	>3	0	0	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/17/13	19/16/9	<u> </u>		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2		
Acid Number (AN) :10:22) Rev: 1	mg KOH/g	ASTM D8045	1.0	0.49	0.49 0.39 0.36 Contact/Location: KEN BESS - STENEWKS			


Report Id: STENEWKS [WUSCAR] 06135661 (Generated: 04/05/2024 01:10:22) Rev: 1


Contact/Location: KEN BESS - STENEWKS




OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	47.3	46.6	46.4
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color						
Bottom						







Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Sample No.

Contact/Location: KEN BESS - STENEWKS

US 66031

Т:

F:

Contact: KEN BESS

ken.bess@steelandpipe.com