




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
MINING
 Machine Id
ME-83 TITAN TRACKMOBILE 1002730817
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	WC0901882	WC0901878	WC0864711
Sample Date	Client Info	26 Mar 2024	12 Feb 2024	13 Nov 2023
Machine Age	hrs Client Info	13079	12684	12645
Oil Age	hrs Client Info	0	0	0
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >90	8	7	6
Chromium	ppm ASTM D5185m >20	<1	<1	<1
Nickel	ppm ASTM D5185m >2	0	0	0
Titanium	ppm ASTM D5185m >2	0	<1	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >20	<1	2	<1
Lead	ppm ASTM D5185m >40	0	0	<1
Copper	ppm ASTM D5185m >330	0	<1	<1
Tin	ppm ASTM D5185m >15	0	0	0
Vanadium	ppm ASTM D5185m	0	0	<1
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 250	<1	0	1
Barium	ppm ASTM D5185m 10	0	10	0
Molybdenum	ppm ASTM D5185m 100	57	54	59
Manganese	ppm ASTM D5185m	<1	0	0
Magnesium	ppm ASTM D5185m 450	467	433	554
Calcium	ppm ASTM D5185m 3000	1660	1492	1621
Phosphorus	ppm ASTM D5185m 1150	1009	999	1079
Zinc	ppm ASTM D5185m 1350	1215	1123	1263
Sulfur	ppm ASTM D5185m 4250	3559	3417	3334

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	3	4	4
Sodium	ppm ASTM D5185m >158	2	<1	1
Potassium	ppm ASTM D5185m >20	<1	1	<1

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.1	0.1	0.1
Nitration	Abs/cm *ASTM D7624 >20	5.8	5.3	5.4
Sulfation	Abs/.1mm *ASTM D7415 >30	18.5	18.3	18.4

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.5	14.1	14.2
Base Number (BN)	mg KOH/g ASTM D2896 8.5	8.3	8.3	8.6







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.4	13.3

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : WC0901882 Received : 02 Apr 2024
 Lab Number : 06136052 Tested : 03 Apr 2024
 Unique Number : 10955517 Diagnosed : 03 Apr 2024 - Wes Davis
 Test Package : CONST (Additional Tests: TBN)

COVIA - GIUNO - 025
 421 MAIN STREET
 GIUNO, AR
 US 72540
 Contact: DANIEL DELGADO
 daniel.delgado@coviacorp.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: