

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id

U1 FD FAN MOTOR 1B

Component Inboard Blower Fluid CHEVRON GST OIL ISO 68 (--- LTR)

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		mounou	in the babb	ourrorite	i illotor y i	· inotor y =
Sample Number		Client Info		WC0915207		
Sample Date		Client Info		01 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	historv1	historv2
PO		ASTM D8184		12		
Iron	nnm	ASTM D5185m	>20	~1		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	nnm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m	220	-1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	AGTM D5105m	> 20	2		
Auminum	ppm	AGTM D5105m	>20	10		
Connor	ppm	AGTM DE105m	>20	12		
Copper	ррпі	ACTM DE105m	>20	- 4		
	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		3		
Phosphorus	ppm	ASTM D5185m		<1		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		818		
CONTAMINANTS		method	limit/base	current	historv1	history2
Cilicon		ACTM DE105m	. 15	4	inecci y i	
Silicon	ppm	AGTM DE105m	>15	<1		
Botooo	ppm		. 20	<1		
Folassium	ppm		>20	4		
water ppm Water	70 DDD	ASTIVI D6304		0.002		
ppm water	ррп	ASTIVI D0304		22		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	<u> </u>		
Particles >6µm		ASTM D7647	>640	375		
Particles >14µm		ASTM D7647	>80	16		
Particles >21µm		ASTM D7647	>20	3		
Particles >38µm		ASTM D7647	>4	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>18/16/13	9/16/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045		0.071		

Report Id: SALGLE [WUSCAR] 06136360 (Generated: 07/17/2024 07:52:11) Rev: 1

).071 Contact/Location: NEAL HANCOCK - SALGLE



Water

Water (

OIL ANALYSIS REPORT

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

NEG

NEG

71.6

no image

no image

no image

no image

18 18

14

:1999 Cle



* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SALGLE [WUSCAR] 06136360 (Generated: 07/17/2024 07:52:11) Rev: 1

Contact/Location: NEAL HANCOCK - SALGLE

7302 W NORTHERN AVE GLENDALE, AZ US 85303 Contact: NEAL HANCOCK neal.hancockjr@srpnet.com T: (602)236-3238 E:

