

# **OIL ANALYSIS REPORT**

Acid Number (AN) mg KOH/g ASTM D8045 0.622



NORMAL



# SYNOIL 8K

# KAESER SM 10 704656 - BIO-TECH RESOURCES (S/N 1289)

Component Compressor

#### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Woor

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


			Dec2023	Mat2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCZ06136481	UCZ06044112	
Sample Date		Client Info		26 Mar 2024	13 Dec 2023	
Machine Age	hrs	Client Info		39541	37092	
Oil Age	hrs	Client Info		4851	2352	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	<1	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	0	2	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	4	3	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0.3	0	0	
Barium	ppm	ASTM D5185m	0.3	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	0.9	0	0	
Magnesium	ppm	ASTM D5185m	0.2	0	1	
Calcium	ppm	ASTM D5185m	0.1	0	<1	
Phosphorus	ppm	ASTM D5185m	429	293	361	
Zinc	ppm	ASTM D5185m	0.3	0	0	
Sulfur	ppm	ASTM D5185m	1336	3346	4210	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	
Sodium	ppm	ASTM D5185m		0	<1	
Potassium	ppm	ASTM D5185m	>20	0	2	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.71

0.63




# **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	MODER	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
<b>Emulsified Water</b>	scalar	*Visual	>0.05	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	44.32	48.5	48.2	
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				a.	0.	no image


## **GRAPHS**

**Bottom** 













Certificate L2367

Laboratory Sample No.

Lab Number : 06136481 Unique Number : 10955946

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCZ06136481

Received **Tested** Test Package : IND 2

: 02 Apr 2024 Diagnosed

: 03 Apr 2024 : 04 Apr 2024 - Sean Felton

**ZORN COMP & EQUIPMENT CO (GB)** 733 POTTS AVE GREEN BAY, WI

US 54304 Contact: DEAN SCHAD dean.schad@zornair.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (920)499-1168 Contact/Location: DEAN SCHAD - UCZORGRE

T: (920)391-8121

no image