

OIL ANALYSIS REPORT

Sample Rating Trend





VOLVO A25D 742205 Component Hydraulic System

VOLVO SUPER HYDRAULIC OIL 46 (--- GAL)

DIAGNOSIS Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0000458		
Sample Date		Client Info		26 Mar 2024		
Machine Age	hrs	Client Info		4305		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
· ·			11 11 11	-		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	10		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	3		
Copper	ppm	ASTM D5185m	>150	5		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	14	0		
Barium	ppm	ASTM D5185m	0.0	0		
Molybdenum	ppm	ASTM D5185m	0.0	0		
Manganese	ppm	ASTM D5185m	0.0	0		
Magnesium	ppm	ASTM D5185m	2.6	0		
Calcium	ppm	ASTM D5185m	49	71		
Phosphorus	ppm	ASTM D5185m	354	339		
Zinc	ppm	ASTM D5185m	419	441		
Sulfur	ppm	ASTM D5185m	3719	6103		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	S ppm		limit/base >20	current 4	history1	history2
	ppm				history1 	history2
Silicon		ASTM D5185m	>20	4	history1 	history2
Silicon Sodium	ppm ppm ppm	ASTM D5185m ASTM D5185m	>20	4 4		
Silicon Sodium Potassium FLUID CLEANLIN	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>20 >20	4 4 <1		
Silicon Sodium Potassium FLUID CLEANLIN	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method	>20 >20 limit/base	4 4 <1 current	 history1	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647	>20 >20 limit/base	4 4 <1 current 4169	 history1	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160	4 4 <1 current 4169 320	 history1 	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160	4 4 <1 current 4169 320 17	 history1 	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160 >40 >10	4 4 <1 <u>current</u> 4169 320 17 5	 history1 	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160 >40 >10	4 4 <1 <u>current</u> 4169 320 17 5 0	 history1 	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm	ppm ppm ppm NESS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160 >40 >10 >3	4 4 <1 current 4169 320 17 5 0 0	 history1 	 history2
Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness	ppm ppm ppm NESS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ISO 4406 (c)	>20 >20 limit/base >5000 >160 >40 >10 >3 >3 >/19/14	4 4 <1 current 4169 320 17 5 0 0 0 19/15/11	 history1 	 history2

Report Id: VOLVO0264 [WUSCAR] 06136882 (Generated: 04/05/2024 12:30:45) Rev: 1

Contact/Location: TOMMY GRIFFIN - VOLVO0264



(^B/HOX Ê0.18 -a u 0.12 0.06 0.00 Mar26/24

OIL ANALYSIS REPORT

Particle Trend	VISUAL		method	limit/base	current	history1	history2
4μm	White Metal	scalar	*Visual	NONE	NONE		
κ - ···································	Yellow Metal	scalar	*Visual	NONE	NONE		
k +	Precipitate	scalar	*Visual	NONE	NONE		
k	Silt	scalar	*Visual	NONE	NONE		
k -	Debris	scalar	*Visual	NONE	NONE		
k	Sand/Dirt	scalar	*Visual	NONE	NONE		
Mar26/24	Appearance	scalar	*Visual	NORML	NORML		
Marź	Odor	scalar	*Visual	NORML	NORML		
Acid Number	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
4	FLUID PROPER	TIES	method	limit/base	current	history1	history2
8 -	Visc @ 40°C	cSt	ASTM D445	46	43.4		
2	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Mar26)29,24 +	Color					no image	no image
Viscosity @ 40°C	Bottom					no image	no image
6 d d d d d d d d d d d d d d d d d d d	GRAPHS Ferrous Alloys			491,520 122,880 30,720	Particle Count		-24 -22
Particle Trend	Non-ferrous Meta			7,680 47/92/em 47/92/em 480 480 480 480 480 480 480			-20 -18 -16 -14 -12
Marc6/24	Viscosity @ 40°C			30 Harris 20 472 2 2 0 2 0 2 0 2 1 1 1 1 1 1 1 1 1 1 1 1 1	Bioresemal	14μ 21μ	12 10
	Abnomal Base 40 40 40 40 40 40 40 40 40 40			(0.30 (0.40) 0.24 (0.40) 0.18 	Acid Number		Max6774
	: ML0000458 r : 06136882 sr : 10956347 e : CONST rt, contact Customer Serv at are outside of the ISO 1	Rece Teste Diagr vice at 1-8	ived : 02 ed : 03 nosed : 04 800-237-1369 ope of accred	2 Apr 2024 3 Apr 2024 Apr 2024 - Don 9. <i>litation</i> .	Baldridge	CHE Contact: TO tgriffin@mccl T:	CO-CHESAPEAKI OLLAND BLVE SAPEAKE, VA US 23323 MMY GRIFFIN ung-logan.com (757)485-3314 (757)485-3415

Report Id: VOLVO0264 [WUSCAR] 06136882 (Generated: 04/05/2024 12:30:45) Rev: 1

Contact/Location: TOMMY GRIFFIN - VOLVO0264