

OIL ANALYSIS REPORT



Component Diesel Engine Fluid DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Machine Id 2106

Recommendation

No corrective action is recommended at this time. We recommend an early resample to monitor this condition. Sample submitted as an engine but data appears to be from a gearbox.

A Wear

The iron level is abnormal.

Contamination

Elemental level of silicon (Si) above normal indicating ingress of seal material.

Fluid Condition

The oil viscosity is higher than normal. Additive levels indicate the addition of a different brand, or type of oil. The BN result indicates that there is suitable alkalinity remaining in the oil.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0894004	WC0894002	WC0893977
Sample Date		Client Info		21 Mar 2024	21 Mar 2024	27 Feb 2024
Machine Age	mls	Client Info		0	0	0
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	NORMAL	NORMAL
CONTAMINATION	١	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	000	ACTM DE105m	. 100	A 010	1	4
Chromium	ppin	AGTM DE105m	>100	2 313	4	4
Niekol	ppin	AGTIM D5105III	>20	2	0	0
Titonium	ppm	ASTM DE105m	>4	-1	0	0
Silver	ppm	ASTM DE185m	~3	<1	0	0
Aluminum	ppin	AGTM DE105m	>0	0	-1	-1
Auminum	ppin	AGTIM DE105m	>20	0	< 1	< 1
Canaar	ррп		>40	0	0	0
Copper	ppm	ASTM DE185m	>330	15	<1	0
	ppm		>15	U	U	< 1
Vanadium	ppm			<1	< 1	0
Cadmium	ppm	ASTM D5185m		U	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	178	0	0
Barium	ppm	ASTM D5185m	10	2	0	0
Molybdenum	ppm	ASTM D5185m	100	4	63	59
Manganese	ppm	ASTM D5185m		9	0	0
Magnesium	nnm					
Coloium	ppin	ASTM D5185m	450	57	1034	1050
Calcium	ppm	ASTM D5185m ASTM D5185m	450 3000	57 79	1034 1147	1050 1135
Phosphorus	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	450 3000 1150	57 79 1278	1034 1147 1099	1050 1135 1099
Phosphorus Zinc	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	450 3000 1150 1350	57 79 1278 191	1034 1147 1099 1357	1050 1135 1099 1279
Phosphorus Zinc Sulfur	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	450 3000 1150 1350 4250	57 79 1278 191 24513	1034 1147 1099 1357 3782	1050 1135 1099 1279 3194
Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method	450 3000 1 1150 1350 0 4250 1 limit/base	57 79 1278 191 24513 current	1034 1147 1099 1357 3782 history1	1050 1135 1099 1279 3194 history2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	450 3000 1150 1350 4250 limit/base >25	57 79 1278 191 24513 current 141	1034 1147 1099 1357 3782 history1 4	1050 1135 1099 1279 3194 history2 2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D5185m ASTM D5185m	450 3000 1 1150 1350 4 4250 1 limit/base >25 >158	57 79 1278 191 24513 current ↓ 141 2	1034 1147 1099 1357 3782 history1 4 2	1050 1135 1099 1279 3194 history2 2 2 2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	450 3000 1150 1350 4250 1 limit/base >25 >158 >20	57 79 1278 191 24513 current 141 2 <1	1034 1147 1099 1357 3782 history1 4 2 <1	1050 1135 1099 1279 3194 history2 2 2 2 0
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	450 3000 1150 4250 imit/base >25 >158 >20 imit/base	57 79 1278 191 24513 current 141 2 <1 current	1034 1147 1099 1357 3782 history1 4 2 <1 history1	1050 1135 1099 1279 3194 history2 2 2 2 0 history2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844	450 3000 1 1150 4250 4 25 >25 >158 >20 limit/base >3	57 79 1278 191 24513 current 141 2 <1 current 0.1	1034 1147 1099 1357 3782 history1 4 2 <1 kistory1 0.2	1050 1135 1099 1279 3194 history2 2 2 2 0 history2 0.2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm % Abs/cm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844	450 3000 1150 1350 4250 1 225 >158 20 1imit/base >20 1imit/base >3 >20	57 79 1278 191 24513 current ↓ 141 2 <1 current 0.1 5.6	1034 1147 1099 1357 3782 history1 4 2 <1 4 2 <1 history1 0.2 8.6	1050 1135 1099 1279 3194 history2 2 2 2 2 0 history2 0.2 8.6
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7624	450 3000 1150 1350 4250 imit/base >25 >158 >20 imit/base >3 >20	57 79 1278 191 24513 <u>current</u> 141 2 <1 <u>current</u> 0.1 5.6 98.3	1034 1147 1099 1357 3782 history1 4 2 <1 history1 0.2 8.6 20.9	1050 1135 1099 1279 3194 history2 2 2 2 0 history2 0.2 8.6 20.7
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844 *ASTM D7624 *ASTM D7415	450 3000 1150 1350 4250 4250 1 225 2 3158 2 20 1 1imit/base 2 33 20 2 30 1	57 79 1278 191 24513 current 141 2 <1 current 0.1 5.6 98.3 current	1034 1147 1099 1357 3782 history1 4 2 <1 history1 0.2 8.6 20.9 history1	1050 1135 1099 1279 3194 history2 2 2 2 0 history2 0.2 8.6 20.7 history2
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA Oxidation	ppm ppm ppm ppm ppm ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844 *ASTM D7415	450 3000 1 1150 1350 4 4250 limit/base >20 limit/base >30 >20 30 limit/base	57 79 1278 191 24513 current 141 2 <1 current 0.1 5.6 98.3 current 93.1	1034 1147 1099 1357 3782 history1 4 2 <1 history1 0.2 8.6 20.9 history1 20.6	1050 1135 1099 1279 3194 history2 2 2 2 2 0 history2 0.2 8.6 20.7 history2 20.4
Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA Oxidation Base Number (BN)	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7624 *ASTM D7624 *ASTM D7415 method *ASTM D7414 ASTM D2896	450 3000 1150 1350 4250 limit/base >25 >158 >20 limit/base >30 limit/base >25 >30	57 79 1278 191 24513 <u>current</u> 141 2 <1 <u>current</u> 0.1 5.6 98.3 <u>current</u> 93.1 10.8	1034 1147 1099 1357 3782 history1 4 2 <1 history1 0.2 8.6 20.9 history1 20.6 7.0	1050 1135 1099 1279 3194 history2 2 2 2 0 history2 0.2 8.6 20.7 history2 20.4 7.4



OIL ANALYSIS REPORT



Contact/Location: Robert Iosiniecki - GODDUR

Page 2 of 2