


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id WW ACP (S/N CBV578862)

Air Compressor

USPI AIR 46 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a trace of moisture present in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun2022 Oct	2022 Feb2023 Jul2023	Oct2023 Nov2023 Nov2023 Dec20	23 Apr2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USPM36612	USP0004436	USPM31292
Sample Date		Client Info		02 Apr 2024	18 Dec 2023	15 Nov 2023
Machine Age	hrs	Client Info		0	0	30802
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>4	<1	0	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	<1
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>40	0	0	<1
Tin	ppm	ASTM D5185m	>5	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	0	0	0	0
Calcium	ppm	ASTM D5185m	0	0	0	<1
Phosphorus	ppm	ASTM D5185m	1	0	<1	1
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	0	0	0	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.2	0.199	0.059	0.058
ppm Water	ppm	ASTM D6304	>2000	1992	599	589.6
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	5671	1779	2960
Particles >6µm		ASTM D7647	>2500	1135	500	656
Particles >14μm		ASTM D7647	>320	294	45	40
Particles >21µm		ASTM D7647		110	15	8
Particles >38μm		ASTM D7647	>20	10	2	0
Particles >71μm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	20/17/15	18/16/13	19/17/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.05	0.08	0.092	0.16



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number

: 06137447

: USPM36612

Unique Number : 10956912 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 03 Apr 2024 **Tested** : 04 Apr 2024

Diagnosed : 04 Apr 2024 - Doug Bogart

928 MARTIN LUTHER KING JR BLVD NACOGDOCHES, TX

US 75961 Contact: KERRI SULLIVAN

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (936)558-6928 Contact/Location: KERRI SULLIVAN - PILNACFRE

PILGRIMS