



# OIL ANALYSIS REPORT

Sample Rating Trend


**NORMAL**



Machine Id  
**SZLK232678**

Component  
**Diesel Engine**

Fluid  
 **DIESEL ENGINE OIL SAE 15W40 (--- QTS)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

Metal levels are typical for a components first oil change.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0905074</b>	---	---
Sample Date	Client Info		<b>11 Mar 2024</b>	---	---
Machine Age	hrs	Client Info	<b>1829</b>	---	---
Oil Age	hrs	Client Info	<b>1829</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Water	WC Method	>0.2	<b>NEG</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>1</b>	---
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	---
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	---
Titanium	ppm	ASTM D5185m		<b>0</b>	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	---
Aluminum	ppm	ASTM D5185m	>20	<b>3</b>	---
Lead	ppm	ASTM D5185m	>40	<b>0</b>	---
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	---
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<b>345</b>	---
Barium	ppm	ASTM D5185m	10	<b>0</b>	---
Molybdenum	ppm	ASTM D5185m	100	<b>119</b>	---
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	---
Magnesium	ppm	ASTM D5185m	450	<b>627</b>	---
Calcium	ppm	ASTM D5185m	3000	<b>1502</b>	---
Phosphorus	ppm	ASTM D5185m	1150	<b>714</b>	---
Zinc	ppm	ASTM D5185m	1350	<b>828</b>	---
Sulfur	ppm	ASTM D5185m	4250	<b>2769</b>	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>4</b>	---
Sodium	ppm	ASTM D5185m	>158	<b>2</b>	---
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	---

## INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.1</b>	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.3</b>	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.2</b>	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>17.0</b>	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>9.5</b>	---







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	13.2	---	---

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0905074      **Received** : 03 Apr 2024  
**Lab Number** : 06137944      **Tested** : 04 Apr 2024  
**Unique Number** : 10962752      **Diagnosed** : 04 Apr 2024 - Wes Davis  
**Test Package** : FLEET

**DOLE FRESH FRUIT**  
 PO BOX 1689  
 GULFPORT, MS  
 US 39502

Contact: JORDAN JOHNSTON  
 jordan.johnston@dole.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (228)867-2970