<u>Sullivan</u> Palatek。

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area **ROTO EXTEND [8016142]** Machine Id **ATLAS COPCO API485590 - FUSION PLASTICS**

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM		method	limit/base	current	history1	history2
		Client Info	innivoase	UCS06138662	UCS05757327	
Sample Number		Client Info		29 Mar 2024	25 Jan 2023	
Sample Date	la va					
Machine Age	hrs	Client Info		39129	33395	
Oil Age	hrs	Client Info		5734	7363	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>5	0	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>15	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	
Copper	ppm	ASTM D5185m	>65	<1	<1	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m		0	0	
Calcium	ppm	ASTM D5185m		0	<1	
Phosphorus	ppm	ASTM D5185m		25	29	
Zinc	ppm	ASTM D5185m		34	23	
Sulfur	ppm	ASTM D5185m		93	95	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	0	<1	
Sodium	ppm	ASTM D5185m		3	0	
Potassium	ppm	ASTM D5185m	>20	0	0	
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045	0.14	0.25	0.16	
	niy NOT/y	A0 HVI D0040	0.14	0.25	0.10	



OIL ANALYSIS REPORT

VISUAL



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
- 24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Mar29/24							
2	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
1	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	49.8	50.2	
	SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Mar29/24 +	Color						no image
	Bottom						no image
	Non-ferrous Metals	5		Mar29/24			
	Viscosity @ 40°C			(0,0,3) (0,10,0,0,0,1) (0,10,0,0,0,1) (0,10,0,0,0,1) (0,10,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,	Acid Number		
Laboratory Sample No.	: WearCheck USA - 501 : UCS06138662	1 Madiso Recei		Mar29/24	Jan 25/23 0	LIFT PRO EG	
Lab Number Unique Number licate 12367 Test Package liscuss this sample report,	: 06138662 : 10963470 : IND 2	SIOUX FALLS, SE US 5710 Contact: REUBEN tim@liftproequipment.con T: (605)339-6494					

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) Report Id: UCLIFSIO [WUSCAR] 06138662 (Generated: 04/06/2024 12:34:36) Rev: 1

Contact/Location: REUBEN - UCLIFSIO

F: