

The Outer Banks Hospital [13213] [The Outer Banks Hospital] DAY TANK 2

Diesel Fuel

Fluid No.2 DIESEL FUEL (ULTRALOW SULPHUR) (200 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

Corrosion


All metal levels are normal indicating no corrosion in the system.

Contaminants

There is a moderate amount of particulates present in the fuel. The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample.

Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC06139100		
Sample Date		Client Info		19 Mar 2024		
Machine Age	hrs	Client Info		0		
Sample Status				ATTENTION		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Fuel Color	text	*Visual Screen	Yllow	Red		
ASTM Color	scalar	*ASTM D1500		L4.0		
Visc @ 40°C	cSt	ASTM D445	3.0	2.39		
Pensky-Martens Flash Point	°C	*PMCC Calculated	52	59.9		
SULFUR CONTER	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m	10	0		
Sulfur (UVF)	ppm	ASTM D5453		8		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D86	165	170		
5% Distillation Point	°C	ASTM D86		192		
10% Distill Point	°C	ASTM D86	201	202		
15% Distillation Point	°C	ASTM D86		210		
20% Distill Point	°C	ASTM D86	216	218		
30% Distill Point	°C	ASTM D86	230	233		
40% Distill Point	°C	ASTM D86	243	247		
50% Distill Point	°C	ASTM D86	255	260		
60% Distill Point	°C	ASTM D86	267	275		
70% Distill Point	°C	ASTM D86	280	289		
80% Distill Point	°C	ASTM D86	295	304		
85% Distillation Point	°C	ASTM D86		315		
90% Distill Point	°C	ASTM D86	310	326		
95% Distillation Point		ASTM D86		344		
Final Boiling Point	°C	ASTM D86	341	358		
IGNITION QUALI	ΓY	method	limit/base	current	history1	history2
API Gravity		ASTM D7777	37.7	37		
Cetane Index		ASTM D4737	<40.0	48		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	0		
Sodium	ppm	ASTM D5185m	<0.1	<1		
Potassium	ppm	ASTM D5185m	<0.1	0		
Water	%	ASTM D6304	<0.05	0.003		
ppm Water	ppm	ASTM D6304	<500	28		
% Gasoline	%	*In-House	<0.50	0.0		
% Biodiesel	%	*In-House	<20.0	0.0		



FUEL REPORT

401 520	Particle Count		
491,520 122,880			- -
Ê 30,720		28	
7,680	Abnormal 12	8	
aptire 480		99 Clea	
1,920 1,920 1,920 480 120 120 30 30		nee r	
umu 8		0 E P	
2		()
04	μ 6μ 14μ 21μ 38μ 71μ		
- 3k	Particle Trend	<i>F</i>	4
-	Honomaa 4µm	١	
number of particles (1 ml) 3k 3k 37 3k 38	14μm	. L	
apitue 2k		١	/
jo ja 1k		1	
1k		(
0k		N	
	Mar ¹ 9/24	Mar19/24 -	
	Ma	Marl	-
1000	Water (KF)		
1200 1000	Severe		
		(2
(mda (ppm) 400			
ate ∧ 400	Abnormal		
200			
0		=_ E	3
	Mar ¹ 9/24	Mar19/24	
	Ma	Ma	
	Viscosity @ 40°C	00000	
6		380°C	I
5	Abnormal	360°C	İ
cSt (40°C)	Base	340°C	
ts 2	Abnormal	320°C	ł
1		300°C	
0		280°C	
	Mar19/24	Mar19/24 i.emperature (*) 0.097 0.097 0.092	
	Mai	eW telad 240°C	ļ
	Gas Chromatography (GCD)	. <u>ଇ</u> 220°C	
400	GCD 10%	200°C	
350	GCD 50%	or -	Ī
ت 300 ئ		180°C	
ງ. auton 250		160°C	Í
₽ 200		140°C	ł
150		120°C	1
190	Mar1 9/24	Mar19/24	1
	Mari	Mari	

	FLUID CLEANL	INESS	method	limit/bas	se current	history1	history
-24	Particles >4µm		ASTM D7647	>2500	2387		
1SO 4406:1999 Cleanliness Code	Particles >6µm		ASTM D7647	>640	— 702		
06:199	Particles >14µm		ASTM D7647	>80	96		
99 Clea	Particles >21µm		ASTM D7647	>20	<mark> </mark> 45		
anlines	Particles >38µm		ASTM D7647	>4	3		
2	Particles >71µm		ASTM D7647	>3	0		
	Oil Cleanliness		ISO 4406 (c)	>18/16/13	3 🛑 18/17/14		
	HEAVY METAL	S	method	limit/bas	se current	history1	history
	Aluminum	ppm	ASTM D5185m	<0.1	0		
	Nickel	ppm	ASTM D5185m	<0.1	0		
	Lead	ppm	ASTM D5185m	<0.1	0		
	Vanadium	ppm	ASTM D5185m	<0.1	0		
	Iron	ppm	ASTM D5185m	<0.1	0		
	Calcium	ppm	ASTM D5185m	<0.1	0		
	Magnesium	ppm	ASTM D5185m	<0.1	0		
	Phosphorus	ppm	ASTM D5185m	<0.1	0		
	Zinc	ppm	ASTM D5185m	<0.1	0		
	SAMPLE IMAGE	ES	method	limit/bas	se current	history1	history
	Color					no image	no imag
	Bottom					no image	no imag
	GRAPHS						
38	Fuel Distillation C	Curve			Pensky-Marter	ıs Flash Point ((°C)
	S0°CBaseline				and the second s		
34	+0°C -			1.	Base 50		
				11	40		
32	20°C -		/		Mar1 9/2 4		
30	- 0°00		1.				
28	30°C -		1.		GCD Spectrum		
Mar19/24 +	30°C -	1	· · ·		550 10'6 190		
Deratu	1000	1			500-		
					450-		
22	20°C			N U	330 300 250		
20	00°C - /			0000	8 300 -		
18	30°C -			Loo D	월 250 - · · · · · · · · · · · · · · · · · ·		
	50°C				200 -		
					100		
	10°C -				50-	V	
							- 10 Y 10 10 10



 Lab Number
 : 06139100
 Tested
 : 15 Apr 2024

 Unique Number
 : 10963908
 Diagnosed
 : 15 Apr 2024 - Doug Bogart

 Certificate 12367
 Test Package
 : DF-2 (Additional Tests: Fuel, Screen)

 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

210 POWELL DR SUMMERVILLE, SC US 29483 Contact: AJAY EL Ajay@prsfuel.com T: (843)225-1777 F:

Contact/Location: AJAY EL - PETSUM