


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# **KAESER 4702375**

Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

### **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

|                  |          |              |            | Apr2024           |          |          |
|------------------|----------|--------------|------------|-------------------|----------|----------|
|                  |          |              |            |                   |          |          |
| SAMPLE INFORM    | MATION   | method       | limit/base | current           | history1 | history2 |
| Sample Number    |          | Client Info  |            | KCPA016279        |          |          |
| Sample Date      |          | Client Info  |            | 01 Apr 2024       |          |          |
| Machine Age      | hrs      | Client Info  |            | 52599             |          |          |
| Oil Age          | hrs      | Client Info  |            | 4000              |          |          |
| Oil Changed      |          | Client Info  |            | Changed           |          |          |
| Sample Status    |          |              |            | ABNORMAL          |          |          |
| WEAR METALS      |          | method       | limit/base | current           | history1 | history2 |
| Iron             | ppm      | ASTM D5185m  | >50        | 0                 |          |          |
| Chromium         | ppm      | ASTM D5185m  | >10        | 0                 |          |          |
| Nickel           | ppm      | ASTM D5185m  | >3         | 0                 |          |          |
| Titanium         | ppm      | ASTM D5185m  |            | 0                 |          |          |
| Silver           | ppm      | ASTM D5185m  | >2         | 0                 |          |          |
| Aluminum         | ppm      | ASTM D5185m  |            | 0                 |          |          |
| Lead             | ppm      | ASTM D5185m  | >10        | 0                 |          |          |
| Copper           |          |              | >50        | 13                |          |          |
| Tin              | ppm      | ASTM D5185m  | >10        | <1                |          |          |
| Vanadium         | ppm      | ASTM D5185m  | >10        | 0                 |          |          |
|                  | ppm      |              |            | -                 |          |          |
| Cadmium          | ppm      | ASTM D5185m  |            | 0                 |          |          |
| ADDITIVES        |          | method       | limit/base | current           | history1 | history2 |
| Boron            | ppm      | ASTM D5185m  | 0          | 0                 |          |          |
| Barium           | ppm      | ASTM D5185m  | 90         | 0                 |          |          |
| Molybdenum       | ppm      | ASTM D5185m  | 0          | 0                 |          |          |
| Manganese        | ppm      | ASTM D5185m  |            | <1                |          |          |
| Magnesium        | ppm      | ASTM D5185m  | 100        | 0                 |          |          |
| Calcium          | ppm      | ASTM D5185m  | 0          | 0                 |          |          |
| Phosphorus       | ppm      | ASTM D5185m  | 0          | <1                |          |          |
| Zinc             | ppm      | ASTM D5185m  | 0          | 0                 |          |          |
| Sulfur           | ppm      | ASTM D5185m  | 23500      | 19977             |          |          |
| CONTAMINANTS     | ;        | method       | limit/base | current           | history1 | history2 |
| Silicon          | ppm      | ASTM D5185m  | >25        | <1                |          |          |
| Sodium           | ppm      | ASTM D5185m  |            | <1                |          |          |
| Potassium        | ppm      | ASTM D5185m  | >20        | 0                 |          |          |
| Water            | %        | ASTM D6304   | >0.05      | 0.003             |          |          |
| ppm Water        | ppm      | ASTM D6304   | >500       | 32                |          |          |
| FLUID CLEANLIN   | IESS     | method       | limit/base | current           | history1 | history2 |
| Particles >4μm   |          | ASTM D7647   |            | 24757             |          |          |
| Particles >6µm   |          | ASTM D7647   | >1300      | <b>14233</b>      |          |          |
| Particles >14µm  |          | ASTM D7647   | >80        | <u>▲</u> 2627     |          |          |
| Particles >21µm  |          | ASTM D7647   | >20        | <b>△</b> 363      |          |          |
| Particles >38µm  |          | ASTM D7647   | >4         | 2                 |          |          |
| Particles >71µm  |          | ASTM D7647   | >3         | 0                 |          |          |
| Oil Cleanliness  |          | ISO 4406 (c) | >/17/13    | <u>^</u> 22/21/19 |          |          |
| FLUID DEGRADA    | TION     | method       | limit/base | current           | history1 | history2 |
|                  |          |              |            |                   |          |          |
| Acid Number (AN) | mg KOH/g | ASTM D8045   | 1.0        | 0.35              |          |          |



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: KCPA016279 Lab Number : 06139262

Unique Number : 10964070 Test Package : IND 2 ( Additional Tests: KF, PrtCount )

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 04 Apr 2024 **Tested** : 05 Apr 2024

Diagnosed : 06 Apr 2024 - Don Baldridge

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: Contact/Location: Service Manager - GREDEP

DE PERE, WI

US 54115

T:

**GREEN BAY PACKAGING** 

2275 AMERICAN BLVD

Contact: Service Manager