




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area

OKLAHOMA/102/EG - OTHER SERVICE

Machine Id
22.64L [OKLAHOMA^102^EG - OTHER SERVICE]

Component

Diesel Engine

Fluid

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	WC0886892	WC0590256	WCCF9909
Sample Date	Client Info	27 Mar 2024	23 Aug 2021	12 Mar 2019
Machine Age	hrs	5800	5390	5141
Oil Age	hrs	410	247	360
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >200	36	25	37
Chromium	ppm ASTM D5185m >20	3	2	2
Nickel	ppm ASTM D5185m >2	<1	0	<1
Titanium	ppm ASTM D5185m >2	<1	<1	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >30	2	2	3
Lead	ppm ASTM D5185m >30	2	2	2
Copper	ppm ASTM D5185m >30	3	2	2
Tin	ppm ASTM D5185m >15	6	4	2
Antimony	ppm ASTM D5185m	---	0	0
Vanadium	ppm ASTM D5185m	<1	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	62	85	62
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 0	39	39	37
Manganese	ppm ASTM D5185m	1	<1	<1
Magnesium	ppm ASTM D5185m 0	493	542	593
Calcium	ppm ASTM D5185m	1643	1716	1562
Phosphorus	ppm ASTM D5185m	742	784	795
Zinc	ppm ASTM D5185m	892	902	912
Sulfur	ppm ASTM D5185m	2531	2383	2378

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	12	12	13
Sodium	ppm ASTM D5185m	3	<1	5
Potassium	ppm ASTM D5185m >20	3	3	4

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.4	0.3	0.2
Nitration	Abs/cm *ASTM D7624 >20	6.6	6.3	6.4
Sulfation	Abs/.1mm *ASTM D7415 >30	21.8	20.9	21.1


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	19.9	18.8	19
Base Number (BN)	mg KOH/g ASTM D2896 9.4	10.1	9.9	10.2




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445 14	12.5	13.0	12.75

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WC0886892

Lab Number : 06139463

Unique Number : 10964271

Test Package : CONST (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

SHERWOOD CONSTRUCTION CO INC

3219 WEST MAY ST

WICHITA, KS

US 67213

Contact: DOUG KING

doug.king@sherwood.net

T: (316)617-3161

F: x: