




OIL ANALYSIS REPORT

Sample Rating Trend



WEAR



Area

Building 12

Machine Id

Conveyor 3

Component

Drive End Conveyor Gearbox

Fluid

SCHAEFFER 293A SUPREME GEAR LUBE NO TACK 220 (11 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. (Customer Sample Comment: Top Up Amount: GAL)

Wear

The iron level has decreased, but is still abnormal. Gear wear is indicated.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0901957	WC0820066	WC0782538
Sample Date	Client Info		28 Feb 2024	04 Sep 2023	02 Apr 2023
Machine Age	hrs	Client Info	0	0	0
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info		Oil Added	Not Chngd	N/A
Sample Status			ABNORMAL	SEVERE	SEVERE

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >200	▲ 278	▲ 890	▲ 1149
Chromium	ppm	ASTM D5185m >10	1	5	7
Nickel	ppm	ASTM D5185m >10	0	2	4
Titanium	ppm	ASTM D5185m	0	<1	<1
Silver	ppm	ASTM D5185m	0	0	0
Aluminum	ppm	ASTM D5185m	6	10	18
Lead	ppm	ASTM D5185m	0	0	0
Copper	ppm	ASTM D5185m	2	1	2
Tin	ppm	ASTM D5185m	0	0	0
Vanadium	ppm	ASTM D5185m	0	0	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	39	55	90
Barium	ppm	ASTM D5185m	0	0	0
Molybdenum	ppm	ASTM D5185m	237	286	345
Manganese	ppm	ASTM D5185m	3	11	14
Magnesium	ppm	ASTM D5185m	2	5	19
Calcium	ppm	ASTM D5185m	6	5	15
Phosphorus	ppm	ASTM D5185m	610	906	1072
Zinc	ppm	ASTM D5185m	3	23	46
Sulfur	ppm	ASTM D5185m	23168	27349	27126

CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	22	21	▲ 61
Sodium	ppm	ASTM D5185m	2	3	6
Potassium	ppm	ASTM D5185m >20	0	0	2

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.30	1.70	1.83



OIL ANALYSIS REPORT





VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	MODER	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 213	223	211	224

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color					
Bottom					



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0901957 **Received** : 05 Apr 2024
Lab Number : **06140073** **Tested** : 08 Apr 2024
Unique Number : 10964881 **Diagnosed** : 08 Apr 2024 - Don Baldrige
Test Package : IND 2

3M - PITTSBORO
 4191 NC 87 S
 MONCURE, NC
 US 27559
 Contact: CHARLES JARRELL
 cjarrell@mmm.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)