

OIL ANALYSIS REPORT



Machine Id

KAESER SFC 315S 6081794 (S/N 1014)

Component Compressor Fluid

KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC06141337	KC100289	KC73009
Sample Date		Client Info		02 Apr 2024	08 Apr 2022	10 May 2021
Machine Age	hrs	Client Info		45635	32228	25816
Oil Age	hrs	Client Info		0	6412	6200
Oil Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>50	0	-1	0
Chromium	nnm	ASTM D5185m	>10	0	0	0
Nickel	nnm	ASTM D5185m	>3	0	0	0
Titanium	nnm	ASTM D5185m	>3	0	0	0
Silver	nnm	ASTM D5185m	>2	0	<1	<1
Aluminum	nnm	ASTM D5185m	<u>>10</u>	0	~1	0
Lead	nnm	ASTM D5185m	>10	0	0	0
Copper	nnm	ASTM D5185m	>50	2	1	6
Tin	nnm	ASTM D5185m	>10	0	-1	0
Antimony	nnm	ASTM D5185m	210			0
Vanadium	nnm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
	ррш	AUTIVI DUTUUIII		U	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	1	0
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	90	0	0	0
Calcium	ppm	ASTM D5185m	2	0	0	0
Phosphorus	ppm	ASTM D5185m		0	3	0
Zinc	ppm	ASTM D5185m		10	22	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	3
Sodium	ppm	ASTM D5185m		1	6	3
Potassium	ppm	ASTM D5185m	>20	0	8	6
Water	%	ASTM D6304	>0.05	0.006	0.032	0.013
ppm Water	ppm	ASTM D6304	>500	62	325.8	132.9
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		1108	1026	92
Particles >6µm		ASTM D7647	>1300	286	291	23
Particles >14µm		ASTM D7647	>80	18	14	4
Particles >21µm		ASTM D7647	>20	3	4	2
Particles >38µm		ASTM D7647	>4	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	17/15/11	15/11	12/9
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.36	0.33	0.333

Contact/Location: Service Manager - AGRMED Page 1 of 2



OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	43.6	41.6	43.4
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color)
Pottom						

ottom



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: AGRMED [WUSCAR] 06141337 (Generated: 04/10/2024 18:29:56) Rev: 1

Certificate 12367

Contact/Location: Service Manager - AGRMED Page 2 of 2

F: