

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area **S-460 [9091]** Machine Id **KAESER 1048 - AMAZON**

Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UDI06141425	UCH05885717	
Sample Date		Client Info		01 Apr 2024	19 Jun 2023	
Machine Age	hrs	Client Info		14911	12117	
Oil Age	hrs	Client Info		2739	4789	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	
Chromium	ppm	ASTM D5185m	>10	0	2	
Nickel	ppm	ASTM D5185m	>3	0	2	
Titanium	ppm	ASTM D5185m	>3	0	2	
Silver	ppm	ASTM D5185m	>2	0	1	
Aluminum	ppm	ASTM D5185m	>10	0	5	
Lead	ppm	ASTM D5185m	>10	0	5	
Copper	ppm	ASTM D5185m	>50	0	3	
Tin	ppm	ASTM D5185m	>10	0	2	
Vanadium	ppm	ASTM D5185m		0	1	
Cadmium	ppm	ASTM D5185m		0	2	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	70	50	
Molybdenum	ppm	ASTM D5185m		0	2	
Manganese	ppm	ASTM D5185m		0	2	
Magnesium	ppm	ASTM D5185m	90	74	60	
Calcium	ppm	ASTM D5185m	2	0	3	
Phosphorus	ppm	ASTM D5185m		0	5	
Zinc	ppm	ASTM D5185m		0	13	
Sulfur	ppm	ASTM D5185m		21020	18810	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	3	
Sodium	ppm	ASTM D5185m		19	16	
Potassium	ppm	ASTM D5185m	>20	3	11	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.37	0.35	



Abnormal 40. 38 36. Jun19/23

OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Apr1/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Ar	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	37.6	44.3	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Apri/24	Color						no image
	Bottom						no image
	GRAPHS						
	Ferrous Alloys						
	8 - iron						
	= 6 - nickel						
	2						
	0	The second second					
	Jun 19/23			Apr1/24			
	lunl			Ap.			
	Non-ferrous Meta	ls					
	10 T						
	8 - copper						
	4 4						
	2	Columnia and a second	Co.dminutererererererererererererererererererer				
	0	and and beatings	NAME OF TAXABLE PARTY.	and the second sec			
	Jun 19/23			Apr1/24			
	-			A			
	Viscosity @ 40°C				Acid Number		
	55			, ^{0.9}			
	50 - Abnormal			.00 .00 .00 .00 .00 .00 .00 .00 .00 .00	40 - Base		
	Good 45			<u>ڦ</u> 0.3	30		
				.0 ge	20		
	40 - 9			N 10.	10		
	35						
	Jun 19/23			Apr1/24	Jun 19/23		
	٦				L.		
Laboratory Sample No.	: WearCheck USA - 50 : UDI06141425	1 Madiso Rece		r, NC 27513 3 Apr 2024	DELTA	NDUSTRIES - C	EDAR RAPID
Lab Number		Teste		Apr 2024			AR RAPIDS, I
Unique Number				Apr 2024 - Ang	gela Borella	0LDF	US 5240
tte L2367 Test Package				le: = 2= : 1400	<u></u>	Contact: MIC	
cuss this sample report,	, contact Customer Serv						c@deltaind.ne
notes test methods that	are outside of the ISO 1	7025 sco	ope of accred	litation.			(319)862-250
ments of conformity to sp	pecifications are based o	on the sin	nple accepta	nce decisior	n rule (JCGM 106	<i>:2012)</i> F:	(319)862-250
6141425 (Generated: 04/10/202	24 17:10:13) Rev: 1			Con	tact/Location: MI	CHAEL FERRIS	

Report Id: UCDELCED [WUSCAR] 06141425 (Generated: 04/10/2024 17:10:13) Rev: 1