


OIL ANALYSIS REPORT

Sample Rating Trend









DECM01BE (S/N ZBA01290) Component

Biogas Engine

CHEVRON HDAX 9500 GAS ENGINE OIL 40 (100 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0732895	WC0732891	WC0732899
Sample Date		Client Info		03 Apr 2024	12 Mar 2024	23 Feb 2024
Machine Age	hrs	Client Info		58345	58147	57725
Oil Age	hrs	Client Info		56062	56062	56062
Oil Changed		Client Info		Changed	Oil Added	Oil Added
Sample Status				NORMAL	SEVERE	NORMAL
CONTAMINATIO	V	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>.11	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>15	3	2	3
Chromium	ppm	ASTM D5185m		0	<1	0
Nickel	ppm	ASTM D5185m	~ 1	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>6	1	4	2
Lead	ppm	ASTM D5185m	>9	- <1	1	0
Copper	ppm	ASTM D5185m		1	2	2
Tin	ppm	ASTM D5185m	>4	- <1	3	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
	le le			-		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES	nnm		limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	limit/base	7	6	5
Boron Barium	ppm	ASTM D5185m ASTM D5185m	limit/base	7 0	6	5 0
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11	6 0 8	5 0 9
Boron Barium Molybdenum Manganese	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11 0	6 0 8 <1	5 0 9 <1
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11 0 29	6 0 8 <1 38	5 0 9 <1 39
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11 0 29 1899	6 0 8 <1 38 2193	5 0 9 <1 39 1931
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11 0 29 1899 290	6 0 8 <1 38 2193 376	5 0 9 <1 39 1931 301
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	7 0 11 0 29 1899 290 361	6 0 8 <1 38 2193 376 490	5 0 9 <1 39 1931 301 377
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m		7 0 11 0 29 1899 290 361 2589	6 0 8 <1 38 2193 376 490 3594	5 0 9 <1 39 1931 301 377 2339
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base	7 0 11 0 29 1899 290 361 2589	6 0 8 <1 38 2193 376 490 3594 history1	5 0 9 <1 39 1931 301 377 2339 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >181	7 0 11 0 29 1899 290 361 2589 current	6 0 8 <1 38 2193 376 490 3594 history1	5 0 9 <1 39 1931 301 377 2339 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >181 >21	7 0 11 0 29 1899 290 361 2589 current 152 <1	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2	5 0 9 <1 39 1931 301 377 2339 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >181 >21 >20	7 0 11 0 29 1899 290 361 2589 current 152 <1	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2	5 0 9 <1 39 1931 301 377 2339 history2 174 1
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	limit/base >181 >21	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m method *ASTM D5185m *ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m	limit/base >181 >21 >20	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m method *ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base >181 >21 >20	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current 0 5.6	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1 7.0	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2 0.1 6.3
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7624 *ASTM D76145	limit/base >181 >21 >20 limit/base	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current 0 5.6 17.1	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1 7.0 21.7	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2 0.1 6.3 19.2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm	ASTM D5185m method *ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7844 *ASTM D7844 *ASTM D7844 *ASTM D7844	limit/base >181 >21 >20	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current 0 5.6 17.1 current	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1 7.0 21.7 history1	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2 0.1 6.3 19.2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA Oxidation	ppm	ASTM D5185m method *ASTM D5185m *ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415 method *ASTM D7414	limit/base >181 >21 >20 limit/base	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current 0 5.6 17.1 current	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1 7.0 21.7 history1 16.7	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2 0.1 6.3 19.2 history2 13.3
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm	ASTM D5185m method *ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7844 *ASTM D7844 *ASTM D7844 *ASTM D7844	limit/base >181 >21 >20 limit/base	7 0 11 0 29 1899 290 361 2589 current 152 <1 <1 current 0 5.6 17.1 current	6 0 8 <1 38 2193 376 490 3594 history1 ▲ 349 2 4 history1 0.1 7.0 21.7 history1	5 0 9 <1 39 1931 301 377 2339 history2 174 1 2 history2 0.1 6.3 19.2 history2




OIL ANALYSIS REPORT












VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.11	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPER	IIIES	method	ilmit/base		nistory i	nistory2	
Visc @ 100°C	cSt	ASTM D445	13.4	12.9	13.9	13.8	


0 T		11111		THE PER			1177
0						Λ	
Severe							
Abnor	mal				A		
0-	1	1			-11	-	Α.
	1	V	V-	~	11	•	V
Mar8/23	/23	/23	/23	/23	/23	/23	/24
	- American	100	III 4	ug23)ct13/	-8	Jan 22





















Certificate 12367

Laboratory Sample No.

: WC0732895 Lab Number : 06141528 Unique Number : 10966336

Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 08 Apr 2024 **Tested**

: 09 Apr 2024 Diagnosed : 10 Apr 2024 - Sean Felton **EDL NA Recips-Decatur** 620 LANDFILL DRIVE TRINITY, AL

US 35673 Contact: JEFF SUMMERS jeff.summers@energydevelopments.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: ENETRI [WUSCAR] 06141528 (Generated: 04/10/2024 14:31:03) Rev: 1

Submitted By: JEFF SUMMERS

T:

F: