

**MAZAK 314201** 

# **OIL ANALYSIS REPORT**

Sample Rating Trend



### Spindel Fluid

FUCHS RENOLIN ZAF B 10 HT ZINC FREE (9 GAL)

## DIAGNOSIS

#### A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### 📥 Wear

Area D17 Machine Id

The copper level is abnormal. All other component wear rates are normal.

#### Contamination

There is no indication of any contamination in the fluid. The amount and size of particulates present in the system are acceptable.

#### Fluid Condition

Zinc level above manufacturer's recommendations. Confirm oil type. The AN level is acceptable for this fluid.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		FCH0000039		
Sample Date		Client Info		27 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	0		
Chromium	ppm	ASTM D5185m	>2	0		
Nickel	ppm	ASTM D5185m	>2	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>2	0		
Lead	ppm	ASTM D5185m	>25	1		
Copper	ppm	ASTM D5185m	>7	<u> </u>		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		3		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		82		
Phosphorus	ppm	ASTM D5185m		341		
Zinc	ppm	ASTM D5185m		<b>6</b> 503		
Sulfur	ppm	ASTM D5185m		2295		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	7		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	<1		
Water	%	ASTM D6304	>0.1	NEG		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	6291		
Particles >6µm		ASTM D7647	>2500	1255		
Particles >14µm		ASTM D7647	>160	90		
Particles >21µm		ASTM D7647	>40	22		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/14	20/17/14		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.793		



600

500

400

E 300

200

100

12 Ê<sup>10</sup>

 of particles (1) 8

har

6k 41

0

491 520

122,880

7.68 particles (per 1

1.92 480

120

30

0.80

0.70

(B/HO)

¶ 0.50

0.40

0.30

흥 0.20

0.10

0.00

40°C)

3 10

VIar77/D

# **OIL ANALYSIS REPORT**



\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCDANLAF [WUSCAR] 06141879 (Generated: 05/09/2024 09:49:15) Rev: 1

Submitted By: GODWIN GEORGE Page 2 of 2

DANA - FAIRFIELD CUSTOM GEARS AND DRIVES

2400 SAGAMORE PKWY S #2400

LAFAYETTE, IN

Contact: Service Manager

Jeffrey.Alexander@fuchs.com

US 47905

T:

F:

21µ

38L

history1

history

history1

no image

no image

current

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

current

current

Particle Count

Acid Number

Mar27/74

NEG

NEG

10.8

history2

history

history2

no image

no imade

4406

:1999 Cle

14