




OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id
KAESER SK 15T 2492697 (S/N 1087)
 Component
Compressor
 Fluid
KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		KCPA001774	KCP38422	KCP25923
Sample Date	Client Info		19 Mar 2024	01 Mar 2022	23 Jan 2020
Machine Age	hrs	Client Info	53696	47432	41303
Oil Age	hrs	Client Info	0	2000	3766
Oil Changed		Client Info	N/A	Changed	Changed
Sample Status			ABNORMAL	ATTENTION	ABNORMAL

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	1	0	1
Chromium	ppm	ASTM D5185m >10	<1	0	0
Nickel	ppm	ASTM D5185m >3	0	0	0
Titanium	ppm	ASTM D5185m >3	<1	0	0
Silver	ppm	ASTM D5185m >2	<1	0	0
Aluminum	ppm	ASTM D5185m >10	2	0	2
Lead	ppm	ASTM D5185m >10	0	0	<1
Copper	ppm	ASTM D5185m >50	4	16	5
Tin	ppm	ASTM D5185m >10	<1	0	0
Antimony	ppm	ASTM D5185m	---	---	0
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	0	0	<1
Barium	ppm	ASTM D5185m 90	2	0	47
Molybdenum	ppm	ASTM D5185m 0	2	0	0
Manganese	ppm	ASTM D5185m	0	0	<1
Magnesium	ppm	ASTM D5185m 100	19	5	70
Calcium	ppm	ASTM D5185m 0	142	0	84
Phosphorus	ppm	ASTM D5185m 0	414	11	145
Zinc	ppm	ASTM D5185m 0	82	29	156
Sulfur	ppm	ASTM D5185m 23500	1070	18275	19480

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	0	2	2
Sodium	ppm	ASTM D5185m	23	4	39
Potassium	ppm	ASTM D5185m >20	12	0	6
Water	%	ASTM D6304 >0.05	0.009	0.011	0.026
ppm Water	ppm	ASTM D6304 >500	95	110.7	264.4






FLUID CLEANLINESS

	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647		9830	5310	9488
Particles >6µm	ASTM D7647	>1300	▲ 1630	1237	▲ 2686
Particles >14µm	ASTM D7647	>80	▲ 196	● 111	▲ 205
Particles >21µm	ASTM D7647	>20	▲ 40	● 35	▲ 57
Particles >38µm	ASTM D7647	>4	1	1	▲ 7
Particles >71µm	ASTM D7647	>3	0	0	▲ 3
Oil Cleanliness	ISO 4406 (c)	>--/17/13	▲ 20/18/15	● 17/14	▲ 19/15

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045 1.0	0.21	0.51	0.628


OIL ANALYSIS REPORT





PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	VLITE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	50.7	49.3 ▲ 57.79

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KCPA001774
Lab Number : 06142215
Unique Number : 10967023
Test Package : IND 2 (Additional Tests: KF, PrtCount)
Received : 08 Apr 2024
Tested : 11 Apr 2024
Diagnosed : 11 Apr 2024 - Don Baldrige

SEVERN AUTO BODY
 220 CHINQUAPIN ROUND RD
 ANNAPOLIS, MD
 US 21401
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)