


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

## **KAESER 6387902**

Component Compressor

KAESER SIGMA (OEM) M-460 (--- QTS)

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jui	2021	Jun2023 Apr202	4	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA016344	KCPA003349	KCP36655
Sample Date		Client Info		04 Apr 2024	26 Jun 2023	02 Jun 2021
Machine Age	hrs	Client Info		12230	8609	2540
Oil Age	hrs	Client Info		0	0	2540
Oil Changed		Client Info		Changed	N/A	Changed
Sample Status				ATTENTION	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	2
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	<1	<1	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	2	2	<1
Lead	ppm	ASTM D5185m	>10	0	0	2
Copper	ppm	ASTM D5185m	>50	9	16	3
Tin	ppm	ASTM D5185m	>10	<1	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	22
Barium	ppm	ASTM D5185m	90	<1	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	<1
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	100	13	7	50
Calcium	ppm	ASTM D5185m	0	3	0	0
Phosphorus	ppm	ASTM D5185m	0	1	1	<1
Zinc	ppm	ASTM D5185m	0	100	70	18
Sulfur	ppm	ASTM D5185m	23500	20725	19838	17737
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	<1
Sodium	ppm	ASTM D5185m		<1	2	13
Potassium	ppm	ASTM D5185m	>20	2	0	4
Water	%	ASTM D6304	>0.05	0.009	0.006	0.023
ppm Water	ppm	ASTM D6304	>500	96	66.2	234.7
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		7256	8526	2387
Particles >6µm		ASTM D7647	>1300	<u>2005</u>	<u>▲</u> 3640	651
Particles >14µm		ASTM D7647	>80	<b>89</b>	<u>194</u>	34
Particles >21µm		ASTM D7647	>20	15	<b>38</b>	7
Particles >38µm		ASTM D7647	>4	0	3	0
Particles >71µm		ASTM D7647	>3	1	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/14</b>	<u>^</u> 20/19/15	17/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



## **OIL ANALYSIS REPORT**







Certificate 12367

Lab Number

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA016344 : 06142252

Unique Number : 10967060

Received : 08 Apr 2024 **Tested** Diagnosed

: 11 Apr 2024

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) To discuss this sample report, contact Customer Service at 1-800-237-1369.

: 11 Apr 2024 - Don Baldridge

GILROY, CA US 95020 Contact: C. GALAS cgalas@imagefirst.com T:

8190 MURRAY RD

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: