

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area XTEND Machine Id ATLAS COPCO API833862 - ARNA Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


| SAMPLE INFORM | NATION | method | limit/base | current | history1 | history2 |
|------------------|----------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UCH06142342 | | |
| Sample Date | | Client Info | | 08 Apr 2024 | | |
| Machine Age | hrs | Client Info | | 26231 | | |
| Oil Age | hrs | Client Info | | 1001 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >5 | <1 | | |
| Nickel | ppm | ASTM D5185m | | 0 | | |
| Titanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | | <1 | | |
| Aluminum | ppm | ASTM D5185m | >15 | 2 | | |
| Lead | ppm | ASTM D5185m | >65 | 0 | | |
| Copper | ppm | ASTM D5185m | >65 | <1 | | |
| Tin | ppm | ASTM D5185m | >10 | <1 | | |
| Vanadium | ppm | ASTM D5185m | | <1 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | 8 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | <1 | | |
| Calcium | ppm | ASTM D5185m | | 5 | | |
| Phosphorus | ppm | ASTM D5185m | | 38 | | |
| Zinc | ppm | ASTM D5185m | | 74 | | |
| Sulfur | ppm | ASTM D5185m | | 31 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >35 | 0 | | |
| Sodium | ppm | ASTM D5185m | | 13 | | |
| Potassium | ppm | ASTM D5185m | >20 | 3 | | |
| FLUID DEGRADA | | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 0.14 | 0.14 | | |



OIL ANALYSIS REPORT

VISUAL





| | | | | | current | | |
|--------------------------|--|----------------------------|----------------------|--|-------------------------|----------------|---------------------------|
| | White Metal | scalar | *Visual | NONE | NONE | | |
| | Yellow Metal | scalar | *Visual | NONE | NONE | | |
| | Precipitate | scalar | *Visual | NONE | NONE | | |
| | Silt | scalar | *Visual | NONE | NONE | | |
| | Debris | scalar | *Visual | NONE | NONE | | |
| | Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| 24 | Appearance | scalar | *Visual | NORML | NORML | | |
| Apr8/24 | Odor | | *Visual | NORML | | | |
| | | scalar | | | NORML | | |
| | Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| 1 | Free Water | scalar | *Visual | | NEG | | |
| | FLUID PROPER | TIES | method | | | | history2 |
| | Visc @ 40°C | cSt | ASTM D445 | 46 | 47.4 | | |
| | SAMPLE IMAGE | ES | method | limit/base | current | history1 | history2 |
| Apr8/24 | Color | | | | | no image | no image |
| | Bottom | | | | | no image | no image |
| | E 6 4 | | | | | | |
| | o - chromium | | | Ap(6)/24 | | | |
| | e f f f f f f f f f f f f f f f f f f f | als | | | | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta | | | Apr0.24 | Acid Number | | |
| | Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta | | | Apr8/24 | Base | | |
| | Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta | | | Apr8/24 | Base | | |
| Laboratory Sample No. | Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C Abnomal Abnomal WearCheck USA - 56 : UCH06142342 | 01 Madisc Rece | ived : 08 | (D)HOX Bull and 0.05 (D)HOX BU | Base | | HINGTON A |
| Sample No. Lab Number | Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C Abnomal Abnomal WearCheck USA - 55 : UCH06142342 : 06142342 | 01 Madisc Rece Teste | ived : 08 ed : 09 | (D)HOX Bull Jack 10,005 (D)HOX 10,005 | Base b200dy AIRMA | 700 WASI | HINGTON A\ ARLSTADT, I |
| Sample No. | Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C Abnomal Abnomal Bate WearCheck USA - 55 : UCH06142342 : 006142342 : 10967150 | 01 Madisc Rece Teste | ived : 08 ed : 09 | (D)HOX Bull and 0.05 (D)HOX BU | Base b200dy AIRMA | 700 WASI CA | HINGTON A |

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRCAR [WUSCAR] 06142342 (Generated: 04/12/2024 08:13:42) Rev: 1

Contact/Location: ELVIN DIAZ - UCAIRCAR

Page 2 of 2

F: (201)342-6241