

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
141538
Component

2 Slewing Gearbox

LIEBHERR GEAR HYPOID 90 EP (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The condition of the oil is acceptable for the time in service.

| | | | | Mar2024 | | |
|------------------|---------|-------------|------------|-------------|----------------|----------|
| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | LM0001430 | | |
| Sample Date | | Client Info | | 03 Mar 2024 | | |
| Machine Age | hrs | Client Info | | 13245 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | J | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.2 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >500 | 12 | | |
| Chromium | ppm | ASTM D5185m | >5 | <1 | | |
| Nickel | ppm | ASTM D5185m | >5 | <1 | | |
| Titanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | | 2 | | |
| Lead | ppm | ASTM D5185m | >5 | - <1 | | |
| Copper | ppm | ASTM D5185m | >35 | 4 | | |
| Tin | ppm | ASTM D5185m | >5 | 1 | | |
| /anadium | ppm | ASTM D5185m | | <1 | | |
| Cadmium | ppm | ASTM D5185m | | <1 | | |
| | ррпп | | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | <1 | | |
| Molybdenum | ppm | ASTM D5185m | | 2 | | |
| Manganese | ppm | ASTM D5185m | | <1 | | |
| Magnesium | ppm | ASTM D5185m | | 6 | | |
| Calcium | ppm | ASTM D5185m | | 24 | | |
| Phosphorus | ppm | ASTM D5185m | | 412 | | |
| Zinc | ppm | ASTM D5185m | | 12 | | |
| Sulfur | ppm | ASTM D5185m | | 21945 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 4 | | |
| Sodium | ppm | ASTM D5185m | | 1 | | |
| Potassium | ppm | ASTM D5185m | >20 | 2 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| 54:22) Rev: 1 | Journal | vioual | | | ocation: RONNY | |





OIL ANALYSIS REPORT






GRAPHS









Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 **Sample No.** : LM0001430 Lab Number : 06143425 Unique Number : 10968233 Test Package : CONST

Received : 09 Apr 2024 Tested Diagnosed

: 10 Apr 2024 : 12 Apr 2024 - Jonathan Hester

15101 NW 112TH AVE HIALEAH GARDENS, FL

US 33018 Contact: RONNY FUNK

ronny.funk@liebherr.com T: (305)817-7566

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: LIEHIA [WUSCAR] 06143425 (Generated: 07/03/2024 12:54:22) Rev: 1

Contact/Location: RONNY FUNK - LIEHIA

LIEBHERR USA CO - Maritime Cranes