

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

KAESER SX 7.5 4311413 (S/N 1009)

Component Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jan 2017	Feb 2018	Feb 2019 Jan 2023	Mar2024	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA015049	KCP54874	KCP00571
Sample Date		Client Info		21 Mar 2024	26 Jan 2023	13 Feb 2019
Machine Age	hrs	Client Info		11097	9714	5802
Oil Age	hrs	Client Info		2000	2000	1000
Oil Changed		Client Info		Changed	Not Changd	Changed
Sample Status				NORMAL	ATTENTION	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1	0	<1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	0	0
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	8	2	2
Tin	ppm	ASTM D5185m	>10	1	0	<1
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m	90	20	29	24
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	90	69	75	70
Calcium	ppm	ASTM D5185m	2	6	1	2
Phosphorus	ppm	ASTM D5185m		2	5	4
Zinc	ppm	ASTM D5185m		17	5	9
Sulfur	ppm	ASTM D5185m		33806	20383	17901
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm		>25	4	1	2
Sodium	ppm	ASTM D5185m		26	24	16
Potassium	ppm	ASTM D5185m	>20	3	5	3
Water	%	ASTM D6304	>0.05	0.009	0.019	0.020
ppm Water	ppm	ASTM D6304	>500	98	196.8	200
FLUID CLEANLI	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		3485	8272	13136
Particles >6µm		ASTM D7647	>1300	948	1907	△ 4403
Particles >14µm		ASTM D7647	>80	42	83	<u>^</u> 728
Particles >21µm		ASTM D7647	>20	12	16	<u>^</u> 218
Particles >38µm		ASTM D7647	>4	1	0	1 0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/17/13	20/18/14	△ 19/17
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2

0.35



OIL ANALYSIS REPORT







Certificate 12367

Laboratory

Sample No. Lab Number

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA015049 : 06144297

Unique Number : 10969105

Received Tested

: 10 Apr 2024 Diagnosed

: 11 Apr 2024 : 11 Apr 2024 - Doug Bogart

Test Package : IND 2 (Additional Tests: KF, PrtCount) To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

US 53214

Contact: ZACH

DUNNS SPORTING GOODS

6034 W NATIONAL AVE

WEST ALLIS, WI

zach@dunnssportinggoods.net T:

F: