


# **OIL ANALYSIS REPORT**

Acid Number (AN)

mg KOH/g ASTM D8045

**ULTRA COOLANT INGERSOLL RAND VK4201U16304 - DURHAM** 

Component Compressor



### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### **Fluid Condition**


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06144444		
Sample Date		Client Info		19 Mar 2024		
Machine Age	hrs	Client Info		40389		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	1		
Copper	ppm	ASTM D5185m	>50	1		
Tin	ppm	ASTM D5185m	>15	1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	500	675		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	0	<1		
Calcium	ppm	ASTM D5185m	0	7		
Phosphorus	ppm	ASTM D5185m	20	<1		
Zinc	ppm	ASTM D5185m	0	7		
Sulfur	ppm	ASTM D5185m	200	291		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1		
Sodium	ppm	ASTM D5185m		58		
Potassium	ppm	ASTM D5185m	>20	6		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.642



## **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2			
White Metal	scalar	*Visual	NONE	NONE					
Yellow Metal	scalar	*Visual	NONE	NONE					
Precipitate	scalar	*Visual	NONE	NONE					
Silt	scalar	*Visual	NONE	NONE					
Debris	scalar	*Visual	NONE	NONE					
Sand/Dirt	scalar	*Visual	NONE	NONE					
Appearance	scalar	*Visual	NORML	NORML					
Odor	scalar	*Visual	NORML	NORML					
Emulsified Water	scalar	*Visual	>0.1	NEG					
Free Water	scalar	*Visual		NEG					
FLUID PROPERTIES method limit/base current history1 history2									
FLUID FROFERI	IES	memou	IIIIII/Dase	current	HISTORY	HISTOLA			
Visc @ 40°C	cSt	ASTM D445	49.4	56.1					
SAMPLE IMAGES		method	limit/base	current	history1	history2			


Color no image no image **Bottom** no image no image **GRAPHS** 

# Ferrous Alloys













Certificate 12367

Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06144444 Unique Number : 10969252

: UCH06144444

Received : 10 Apr 2024 Tested Diagnosed

: 11 Apr 2024 : 12 Apr 2024 - Sean Felton JOHN HENRY FOSTER COMPANY

4700 LEBOURGET STREET SAINT LOUIS, MO US 63134

Contact: RACHEL VON HATTEN rvonhatten@jhf.com

T: (314)593-1267 F: (314)874-0965

Test Package : IND 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)