

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area ULTRA COOLANT Machine Id INGERSOLL RAND UP6-15C-150 (S/N CBV404137)

1 Air Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		JHF0000174		
Sample Date		Client Info		08 Apr 2024		
Machine Age	hrs	Client Info		3359		
Oil Age	hrs	Client Info		3359		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.6	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>4	<1		
Nickel	ppm	ASTM D5185m	>4	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>20	<1		
Copper	ppm	ASTM D5185m	>40	<1		
Tin	ppm	ASTM D5185m	>5	1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	500	527		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	0	<1		
Calcium	ppm	ASTM D5185m	0	7		
Phosphorus	ppm	ASTM D5185m	20	0		
Zinc	ppm	ASTM D5185m	0	10		
Sulfur	ppm	ASTM D5185m	200	309		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4		
Sodium	ppm	ASTM D5185m		40		
Potassium	ppm	ASTM D5185m	>20	2		
		method	limit/base	current	history1	history2
FLUID DEGRADA		methou			Thistory I	Thistory 2



OIL ANALYSIS REPORT

VISUAL





	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Apr8/24 •	Appearance	scalar	*Visual	NORML	NORML		
Apr	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.6	NEG		
	Free Water	scalar	*Visual		NEG		
				11 11 11			
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	49.4	49.1		
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Apr6/24	Color					no image	no image
	Bottom				•	no image	no image
	Non-ferrous Metal	S		Apr8/24			
	udd 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			Apr8/24			
	∼ Viscosity @ 40°C			4	Acid Number		
	70 Severe			<u>,</u> 2.50	Severe		
	65 Abnormal			H 2.00			
	ු 60 + 6 60 + 6 55 55 ∛ 50 + 8 8 8 8 8 8 8 8 8 8			(2.50 (0,110) (0,110) (0,10) (Abnormal		
				- ⁴ 1.00			
	45 . Severe			P 0.50			
	40				24		
	Apr8/24			Apr8/24	Apr8/24		

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCJOHSAI [WUSCAR] 06144460 (Generated: 04/12/2024 14:40:48) Rev: 1

Submitted By: RACHEL VON HATTEN

F: (314)874-0965