

# **FUEL REPORT**

Sample Rating Trend



Machine Id

# **CC-BSR-LAFAYETTE GA**

**Diesel Fuel** 

**DIESEL ENGINE OIL SAE 15W40 (--- QTS)** 

#### Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

#### Corrosion

All metal levels are normal indicating no corrosion in the system.

## Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. There is no indication of any contamination in the fuel.


### **Fuel Condition**


Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.


|               |        |               |            | Apr2024          |          |          |
|---------------|--------|---------------|------------|------------------|----------|----------|
| SAMPLE INFORM | MATION | method        | limit/base | current          | history1 | history2 |
| Sample Number |        | Client Info   |            | WC0663311        |          |          |
| Sample Date   |        | Client Info   |            | 04 Apr 2024      |          |          |
| Machine Age   | hrs    | Client Info   |            | 04 Apr 2024<br>0 |          |          |
| Sample Status | 1110   | Oliotic IIIIo |            | NORMAL           |          |          |
|               |        |               |            |                  |          |          |
| PHYSICAL PROP | ERTIES | method        | limit/base | current          | history1 | history2 |
| ASTM Color    | scalar | *ASTM D1500   |            | L3.5             |          |          |
| Visc @ 40°C   | cSt    | ASTM D445     | 115        | 2.45             |          |          |
| SULFUR CONTE  | NT     | method        | limit/base | current          | history1 | history2 |
| Sulfur        | ppm    | ASTM D5185m   | 4250       | 0                |          |          |
| Sulfur (UVF)  | ppm    | ASTM D5453    |            | 9                |          |          |
| CONTAMINANTS  |        | method        | limit/base | current          | history1 | history2 |
| Silicon       | ppm    | ASTM D5185m   | <1.0       | <1               |          |          |
| Sodium        | ppm    | ASTM D5185m   | <0.1       | <1               |          |          |
| Potassium     | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Water         | %      | ASTM D6304    | < 0.05     | 0.003            |          |          |
| ppm Water     | ppm    | ASTM D6304    | <500       | 26               |          |          |
| % Gasoline    | %      | *In-House     | < 0.50     | 0.0              |          |          |
| % Biodiesel   | %      | *In-House     | <20.0      | 1.1              |          |          |
| HEAVY METALS  |        | method        | limit/base | current          | history1 | history2 |
| Aluminum      | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Nickel        | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Lead          | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Vanadium      | ppm    | ASTM D5185m   | < 0.1      | <1               |          |          |
| Iron          | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Calcium       | ppm    | ASTM D5185m   | < 0.1      | 0                |          |          |
| Magnesium     | ppm    | ASTM D5185m   | <0.1       | 0                |          |          |
| Phosphorus    | ppm    | ASTM D5185m   | <0.1       | <1               |          |          |
| Zinc          | ppm    | ASTM D5185m   | < 0.1      | 0                |          |          |
| SAMPLE IMAGES | 3      | method        | limit/base | current          | history1 | history2 |
| Color         |        |               |            |                  | no image | no image |
| Bottom        |        |               |            |                  | no image | no image |



# **FUEL REPORT**









Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC0663311 Lab Number : 06144773

Unique Number : 10969581

**Tested** Test Package : DF-5 ( Additional Tests: Screen )

Received : 10 Apr 2024 Diagnosed

: 24 Apr 2024

: 24 Apr 2024 - Angela Borella

RALEIGH, NC US 27616 Contact: BRANDON RICE brandon.rice@natpow.com

**NATIONAL POWER CORP** 

4541 PRESLYN DR

F: (919)790-9714

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)