


FUEL REPORT



NORMAL



UNIT 1 Component

Diesel Fuel DIESEL FUEL No. 2 (--- GAL)

Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

Corrosion

Machine Id

All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. There is no indication of any contamination in the fuel.


Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.


| | | | | Mar2024 | | |
|---------------|--------|-------------|------------|-------------|----------|----------|
| | | | | | | |
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0812917 | | |
| Sample Date | | Client Info | | 26 Mar 2024 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Sample Status | | | | NORMAL | | |
| PHYSICAL PROP | ERTIES | method | limit/base | current | history1 | history2 |
| ASTM Color | scalar | *ASTM D1500 | | L4.5 | | |
| Visc @ 40°C | cSt | ASTM D445 | 4.1 | 2.24 | | |
| SULFUR CONTE | NT | method | limit/base | current | history1 | history2 |
| Sulfur | ppm | ASTM D5185m | | 0 | | |
| Sulfur (UVF) | ppm | ASTM D5453 | | 12 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | <1.0 | <1 | | |
| Sodium | ppm | ASTM D5185m | < 0.1 | <1 | | |
| Potassium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Water | % | ASTM D6304 | < 0.05 | 0.003 | | |
| ppm Water | ppm | ASTM D6304 | <500 | 34 | | |
| % Gasoline | % | *In-House | < 0.50 | 2.9 | | |
| % Biodiesel | % | *In-House | <20.0 | 0.0 | | |
| HEAVY METALS | | method | limit/base | current | history1 | history2 |
| Aluminum | ppm | ASTM D5185m | < 0.1 | 0 | | |
| Nickel | ppm | ASTM D5185m | < 0.1 | 0 | | |
| Lead | ppm | ASTM D5185m | <0.1 | 0 | | |
| Vanadium | ppm | ASTM D5185m | <0.1 | <1 | | |
| Iron | ppm | ASTM D5185m | < 0.1 | 0 | | |
| Calcium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Magnesium | ppm | ASTM D5185m | < 0.1 | 0 | | |
| Phosphorus | ppm | ASTM D5185m | <0.1 | <1 | | |
| Zinc | ppm | ASTM D5185m | < 0.1 | 0 | | |
| SAMPLE IMAGES | 5 | method | limit/base | current | history1 | history2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |



FUEL REPORT









Laboratory

Sample No. : WC0812917 Lab Number : 06144781 Unique Number : 10969589

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received **Tested** Diagnosed

: 10 Apr 2024 : 24 Apr 2024

: 24 Apr 2024 - Angela Borella

Contact: BRANDON RICE brandon.rice@natpow.com

NATIONAL POWER CORP

4541 PRESLYN DR

RALEIGH, NC

US 27616

Test Package : DF-5 (Additional Tests: Screen) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (919)790-9714 Contact/Location: BRANDON RICE - NATRAL