


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



4539-1 Component 1 Gearbox Fluid CASTROL RO 150 (--- GAL)

	Λ.	$\sim$ 1		0	0
וט	А	Ы	VО	5	0

Machine Id

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0920090		
Sample Date		Client Info		05 Apr 2024		
Machine Age	mls	Client Info		90787		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	V	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	21		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	5		
Lead	ppm	ASTM D5185m	>50	1		
Copper	ppm	ASTM D5185m	>200	2		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		5		
Molybdenum	ppm	ASTM D5185m		782		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		7		
Calcium	ppm	ASTM D5185m		165		
Phosphorus	ppm	ASTM D5185m		804		
Zinc	ppm	ASTM D5185m		76		
Sulfur	ppm	ASTM D5185m		17471		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	9		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.39		



## **OIL ANALYSIS REPORT**



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	TES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		157		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						
Iron (ppm)			200	Lead (ppm)		
Severe			200	Severe		
400 Severe 200 Abnormal			톮100	Abnormal		
0			-			
Apr5/24			Apr5/24	Apr5/24		Apr5/24
Aluminum (ppm)				Chromium (pp	om)	
Severe			30	Dorono		
Abnormal			E 20	Abnormal		
Apr5/24			Apr5/24	Apr5/24		Apr5/24
			Ap			Ąb
Copper (ppm)			150	Silicon (ppm)		
400 Severe			E 100			
Abnormal			= 50	Abnormal		
Apr5/24 +			Apr5/24	Apr5/24		Apr5/24
₹ Viscosity @ 40°C						Ā
180 T			5/24 +	1		
160			ا <u>ق</u> 1.0	1		
140 Abnormal			Wmb O.			
Apr5/24 1			Apr5/24	5/24		Apr5/24
Apri			Apri	Apr5/2 <sup>4</sup>		Aprè





Certificate 12367

Sample No. : WC0920090 Lab Number : 06145328 Unique Number : 10970136

Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received

: 10 Apr 2024 Tested : 12 Apr 2024 Diagnosed

: 12 Apr 2024 - Jonathan Hester

1148 NEWARK TURNPIKE KEARNY, NJ US 07032

Contact: DAVE GILBERT david.gilbert@alstomgroup.com

**ALSTOM C/O NEW JERSEY TRANSIT** 

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (973)277-0826