


# **OIL ANALYSIS REPORT**



Area
RIG 1 CATERPILLAR 3512 R1-G-01

**Diesel Engine** 

**CHEVRON 15W40 (--- GAL)** 





## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KL0013873	KL0013836	KL0014041
Sample Date		Client Info		20 Mar 2024	16 Feb 2024	11 Jan 2024
Machine Age	days	Client Info		45362	45338	45303
Oil Age	days	Client Info		0	0	0
Oil Changed	5.5.)	Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL
CONTAMINATION	N.	method	limit/base	current	history1	history2
Fuel	N .	WC Method	>5	<1.0	<1.0	<1.0
				<1.0 NEG	NEG	NEG
Water		WC Method	>0.2			
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	2	1	4
Chromium	ppm	ASTM D5185m	>20	0	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	3	4	4
Lead	ppm	ASTM D5185m	>40	0	<1	<1
Copper	ppm	ASTM D5185m	>330	99	<b>△</b> 478	167
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		340	305	364
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		102	117	117
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		499	638	620
Calcium	ppm	ASTM D5185m		1235	1471	1418
Phosphorus	ppm	ASTM D5185m		666	725	727
Zinc	ppm	ASTM D5185m		687	829	792
Sulfur	ppm	ASTM D5185m		2423	2530	2963
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	19	5	7
Sodium	ppm	ASTM D5185m	>50	0	1	0
Potassium	ppm	ASTM D5185m	>20	2	<1	1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	5.9	7.7	5.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.2	23.5	23.0



## **OIL ANALYSIS REPORT**

Oxidation


Sand/Dirt


Odor


Appearance


Free Water


**Emulsified Water** 











FLUID CLEANLINESS	method				history2
Particles >4µm	ASTM D7647	>20000	3027	1731	2819
Particles >6µm	ASTM D7647	>5000	1649	943	1536
Particles >14µm	ASTM D7647	>640	281	161	261
Particles >21µm	ASTM D7647	>160	95	54	88
Particles >38µm	ASTM D7647	>40	15	8	14
Particles >71µm	ASTM D7647	>10	1	1	1
Oil Cleanliness	ISO 4406 (c)	>21/19/16	19/18/15	18/17/15	19/18/15
FLUID DEGRADATION	method	limit/base	current	history1	history2

Base Number (BN)	mg KOH/g	ASTM D2896		10.21	9.17	8.26
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE

16.2

NONE

**NORML** 

**NORML** 

Particle Count

NEG

**NEG** 

18.3

NONE

**NORML** 

NORML

NEG

NEG

15.6

NONE

NORML

**NORML** 

NEG

NEG

Abs/.1mm \*ASTM D7414 >25

scalar \*Visual

scalar \*Visual

\*Visual

\*Visual

\*Visual

scalar

scalar

scalar


FLUID PROPERTIES		method				history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.4	13.1	13.6

NONE


NORML


**NORML** 

>0.2













Certificate 12367

Laboratory Sample No.

: KL0013873 Lab Number : 06145347

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 10 Apr 2024 **Tested** : 15 Apr 2024

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Unique Number : 10970155 Diagnosed : 15 Apr 2024 - Jonathan Hester Test Package : MOB 2 ( Additional Tests: PrtCount )

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Base 0.0

> ODESSA, TX US 79763 Contact: MIKE COMBDEN

CITADEL DRILLING

7550 W I20

mcombden@citadeldrilling.com T: (780)955-5509 F: