

# **OIL ANALYSIS REPORT**

# Sample Rating Trend



# JAX-AGIT035, 10M Reactor

Component **Gearbox** 

Fluid

{not provided} (--- GAL)

# DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

## Contamination

The water content is negligible. There is no indication of any contamination in the oil.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		RP06145954	RP0016959	RP195725
Sample Date		Client Info		20 Mar 2024	20 Dec 2022	21 Aug 2019
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	22	22	18
Chromium	ppm	ASTM D5185m	>15	<1	0	<1
Nickel	ppm	ASTM D5185m	>15	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	4	4	4
Lead	ppm	ASTM D5185m	>100	1	0	0
Copper	ppm	ASTM D5185m	>200	1	<1	<1
Tin	ppm	ASTM D5185m	>25	1	<1	0
Antimony	ppm	ASTM D5185m	>5			0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		1	0	0
Manganese	ppm	ASTM D5185m		1	<1	<1
Magnesium	ppm	ASTM D5185m		47	56	71
Calcium	ppm	ASTM D5185m		5	1	2
Phosphorus	ppm	ASTM D5185m		17	43	7
Zinc	ppm	ASTM D5185m		35	53	21
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	8	10	5
Sodium	ppm	ASTM D5185m		<1	<1	1
Potassium	ppm	ASTM D5185m	>20	2	0	1
Water	%	ASTM D6304	>0.2	0.016	0.009	0.043
ppm Water	ppm	ASTM D6304	>2000	161	90.4	431.7
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.44

Acid Number (AN)


mg KOH/g ASTM D8045


0.48


0.369



# **OIL ANALYSIS REPORT**







VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID PROPE	THES	method	ilmit/base		nistory i	nistory2
Visc @ 40°C	cSt	ASTM D445		298	296	298


SAMPLE IMAGES	method		history2


Color







## **GRAPHS**













Laboratory Sample No.

: RP06145954 Lab Number : 06145954 Unique Number : 10976032

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 11 Apr 2024 **Tested** Diagnosed

: 12 Apr 2024 : 12 Apr 2024 - Wes Davis

**SYMRISE** 601 CRESTWOOD ST JACKSONVILLE, FL US 32208

Test Package : IND 2 Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: ADAM BOVITCH ADAM.BOVITCH@SYMRISE.COM T: (904)924-2765

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ADAM BOVITCH - RENJAC