

OIL ANALYSIS REPORT



AIRLUBE 228 **ATLAS COPCO API617089**

Component Compressor

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORM | //ATION | method | limit/base | current | history1 | history2 |
|------------------|----------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UCH06145967 | | |
| Sample Date | | Client Info | | 15 Mar 2024 | | |
| Machine Age | hrs | Client Info | | 62736 | | |
| Oil Age | hrs | Client Info | | 2500 | | |
| Oil Changed | | Client Info | | Not Changd | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | V | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 2 | | |
| Chromium | ppm | ASTM D5185m | >5 | <1 | | |
| Nickel | ppm | ASTM D5185m | | <1 | | |
| Titanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >15 | 1 | | |
| Lead | ppm | ASTM D5185m | >65 | 1 | | |
| Copper | ppm | ASTM D5185m | >65 | <1 | | |
| Tin | ppm | ASTM D5185m | >10 | 1 | | |
| Vanadium | ppm | ASTM D5185m | | <1 | | |
| Cadmium | ppm | ASTM D5185m | | 1 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 1.5 | 0 | | |
| Barium | ppm | ASTM D5185m | 0 | 2 | | |
| Molybdenum | ppm | ASTM D5185m | 0 | <1 | | |
| Manganese | ppm | ASTM D5185m | 0.3 | <1 | | |
| Magnesium | ppm | ASTM D5185m | 0 | 2 | | |
| Calcium | ppm | ASTM D5185m | 0 | 3 | | |
| Phosphorus | ppm | ASTM D5185m | 406 | 99 | | |
| Zinc | ppm | ASTM D5185m | 0 | <1 | | |
| Sulfur | ppm | ASTM D5185m | 1283 | 512 | | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >35 | <1 | | |
| Sodium | ppm | ASTM D5185m | | 0 | | |
| Potassium | ppm | ASTM D5185m | >20 | 1 | | |
| FLUID DEGRADA | ATION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 0.463 | 1.14 | | |




OIL ANALYSIS REPORT





| VISUAL | | mathad | limit/bass | ou urrant | history | hiotory () |
|-------------------------|--------|-----------|------------|------------|-----------|-------------|
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPERT | IFS | method | limit/base | current | history1 | history2 |
| T LOID I HOT LITT | 120 | motriou | mme base | och i citt | Thotory I | THO LOT Y Z |
| Visc @ 40°C | cSt | ASTM D445 | 47.9 | 48.6 | | |


| SAMPLE IMAGES | method | limit/base | current | history1 | history2 |
|---------------|--------|------------|---------|----------|----------|
| Color | | | | no image | no image |
| Bottom | | | | no image | no image |

GRAPHS













Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06145967

: UCH06145967 Unique Number : 10976045

Received : 11 Apr 2024 Tested

: 12 Apr 2024

Diagnosed : 15 Apr 2024 - Don Baldridge

Test Package : IND 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

AIR TECHNOLOGIES INC (TOL)

1055 CLUSTER DR TOLEDO, OH US 43612

Contact: KEVIN PLISKA kevin.pliska@aircompressors.com

> T: (419)269-1000 F: (614)414-4063