


OIL ANALYSIS REPORT

VISION 8000 HODGE 2303010830 - CS STRUCTURES

Component Compressor



Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|------------------|----------|-------------|------------|-------------|-------------|----------|
| Sample Number | | Client Info | | UHC0000620 | UHC0000722 | |
| Sample Date | | Client Info | | 15 Mar 2024 | 27 Jul 2023 | |
| Machine Age | hrs | Client Info | | 3673 | 873 | |
| Oil Age | hrs | Client Info | | 2800 | 873 | |
| Oil Changed | | Client Info | | N/A | Changed | |
| Sample Status | | | | NORMAL | NORMAL | |
| CONTAMINATION | | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | NEG | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 1 | 4 | |
| Chromium | ppm | ASTM D5185m | >10 | <1 | 0 | |
| Nickel | ppm | ASTM D5185m | | <1 | 0 | |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | |
| Silver | ppm | ASTM D5185m | | 0 | 0 | |
| Aluminum | ppm | ASTM D5185m | >25 | 1 | 0 | |
| Lead | ppm | ASTM D5185m | >25 | 1 | 0 | |
| Copper | ppm | ASTM D5185m | >50 | 1 | <1 | |
| Tin | ppm | ASTM D5185m | >15 | 1 | 0 | |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 1 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | |
| Barium | ppm | ASTM D5185m | | 0 | <1 | |
| Molybdenum | ppm | ASTM D5185m | | <1 | 0 | |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | |
| Magnesium | ppm | ASTM D5185m | | <1 | 2 | |
| Calcium | ppm | ASTM D5185m | | 3 | 0 | |
| Phosphorus | ppm | ASTM D5185m | | 472 | 432 | |
| Zinc | ppm | ASTM D5185m | | 33 | 129 | |
| Sulfur | ppm | ASTM D5185m | | 1206 | 664 | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 4 | 5 | |
| Sodium | ppm | ASTM D5185m | | 0 | <1 | |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 2 | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.41 | 0.22 | |




OIL ANALYSIS REPORT





| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|-----------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE | |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | |
| Silt | scalar | *Visual | NONE | NONE | NONE | |
| Debris | scalar | *Visual | NONE | NONE | NONE | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | |
| Appearance | scalar | *Visual | NORML | NORML | NORML | |
| Odor | scalar | *Visual | NORML | NORML | NORML | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | |
| Free Water | scalar | *Visual | | NEG | NEG | |
| FLUID PROPERT | ΓIES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D445 | | 42.6 | 44.9 | |
| SAMPLE IMAGES | | method | limit/base | current | history1 | history2 |
| Color | | | | | | no image |


GRAPHS

Bottom













Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06145991 Unique Number : 10976069

: UHC0000620 Test Package : IND 2

Received : 11 Apr 2024 **Tested** : 12 Apr 2024

Diagnosed : 15 Apr 2024 - Don Baldridge

Contact: Derik Bray Derik@atlantaaircompressor.com T: (470)252-9952

ATLANTA AIR COMPRESSOR

123 MERCHANTS PARK DR

HOSCHTON, GA

US 30548

F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) no image