


## **OIL ANALYSIS REPORT**

## Sample Rating Trend



## NORMAL





# Grand Blanc CAT 6 GBLM06BE

Biogas Engine

CHEVRON HDAX 9500 GAS ENGINE OIL 40 (--- GAL)

## DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0905752	WC0905747	WC0905682
Sample Date		Client Info		10 Apr 2024	03 Apr 2024	05 Mar 2024
Machine Age	hrs	Client Info		92909	92740	92124
Oil Age	hrs	Client Info		0	0	91406
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				NORMAL	NORMAL	ABNORMAL
CONTAMINATION	J	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	21.0	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
				NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>14	6	3	5
Chromium	ppm	ASTM D5185m	>3	<1	0	0
Nickel	ppm	ASTM D5185m		1	0	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>5	2	2	3
Lead	ppm	ASTM D5185m	>8	2	0	2
Copper	ppm	ASTM D5185m	>5	2	1	1
Tin	ppm	ASTM D5185m	>3	2	0	2
Vanadium	ppm	ASTM D5185m		<1	<1	0
Cadmium	ppm	ASTM D5185m		1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		3	4	2
Barium	ppm	ASTM D5185m		0	0	0
		ASTM D5185m ASTM D5185m		0 4	0	0
Molybdenum	ppm				2	
Molybdenum Manganese	ppm	ASTM D5185m		4		2
Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m		4	2 0 5	2
Molybdenum Manganese Magnesium Calcium	ppm ppm ppm	ASTM D5185m ASTM D5185m		4 1 7 1784	2 0 5 1660	2 0 7 1925
Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m		4 1 7 1784 281	2 0 5 1660 226	2 0 7 1925 270
Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m		4 1 7 1784	2 0 5 1660	2 0 7 1925
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	4 1 7 1784 281 327 3123	2 0 5 1660 226 301 2687	2 0 7 1925 270 327 3127
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	4 1 7 1784 281 327 3123 current	2 0 5 1660 226 301 2687 history1	2 0 7 1925 270 327 3127 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm	ASTM D5185m	>180	4 1 7 1784 281 327 3123 current	2 0 5 1660 226 301 2687 history1	2 0 7 1925 270 327 3127 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	>180 >20	4 1 7 1784 281 327 3123 current 99	2 0 5 1660 226 301 2687 history1 59	2 0 7 1925 270 327 3127 history2 163 3
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm	ASTM D5185m	>180 >20 >20	4 1 7 1784 281 327 3123 current 99 14	2 0 5 1660 226 301 2687 history1 59 16 <1	2 0 7 1925 270 327 3127 history2 163 3
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m	>180 >20	4 1 7 1784 281 327 3123 current 99 14 7	2 0 5 1660 226 301 2687 history1 59 16 <1	2 0 7 1925 270 327 3127 history2 163 3 0
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  Method ASTM D5185m	>180 >20 >20	4 1 7 1784 281 327 3123 current 99 14 7	2 0 5 1660 226 301 2687 history1 59 16 <1 history1	2 0 7 1925 270 327 3127 history2 163 3 0 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  method ASTM D5185m	>180 >20 >20	4 1 7 1784 281 327 3123 current 99 14 7 current	2 0 5 1660 226 301 2687 history1 59 16 <1 history1 0 5.5	2 0 7 1925 270 327 3127 history2 163 3 0 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  Method ASTM D5185m	>180 >20 >20	4 1 7 1784 281 327 3123 current 99 14 7	2 0 5 1660 226 301 2687 history1 59 16 <1 history1	2 0 7 1925 270 327 3127 history2 163 3 0 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  method ASTM D5185m	>180 >20 >20	4 1 7 1784 281 327 3123 current 99 14 7 current	2 0 5 1660 226 301 2687 history1 59 16 <1 history1 0 5.5	2 0 7 1925 270 327 3127 history2 163 3 0 history2
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  Method  ASTM D5185m  Method  *ASTM D7844  *ASTM D7624  *ASTM D7415	>180 >20 >20   selection   sel	4 1 7 1784 281 327 3123 current 99 14 7 current 0 5.8 22.1	2 0 5 1660 226 301 2687 history1 59 16 <1 history1 0 5.5 19.7	2 0 7 1925 270 327 3127 history2 163 3 0 history2 0 6.1 27.3
Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m  Method  ASTM D5185m ASTM D5185m  ASTM D5185m  ASTM D5185m  ASTM D5185m  ASTM D5185m  ASTM D5185m  Method  *ASTM D7844  *ASTM D7624  *ASTM D7415  Method  *ASTM D7414	>180 >20 >20   selection   sel	4 1 7 1784 281 327 3123 current 99 14 7 current 0 5.8 22.1	2 0 5 1660 226 301 2687 history1 59 16 <1 history1 0 5.5 19.7 history1	2 0 7 1925 270 327 3127 history2 163 3 0 history2 0 6.1 27.3




## **OIL ANALYSIS REPORT**












VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual		NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPER	HES	method			history1	history2
Visc @ 100°C	cSt	ASTM D445	13.4	13.5	13.2	14.0


Sever	e						
Abno	rmal				11111		1111
			Λ				
			/1				
1	1	N	1	1		^	
Mar13/23	Apr26/23	×	Aug7/23	Oct5/23	Nov24/23	Jan17/24 ->	Feb20/24 -
























Certificate 12367

Laboratory Sample No.

: WC0905752 Lab Number : 06146062 Unique Number : 10976140

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received **Tested** 

: 11 Apr 2024 : 12 Apr 2024 Diagnosed : 15 Apr 2024 - Sean Felton

**EDL NA Recips-Grand Blanc** Grand Blanc Powerstation, 2361 West Grand Blanc Road Grand Blanc, MI US 48439

Test Package : MOB 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

tony.saintmarie@edlenergy.com

Contact: Tony Saint Marie

T:

F: