

OIL ANALYSIS REPORT

CODT

Sample Rating Trend

NORMAL



S-460 [8900] Machine 10 [8900] KAESER 1204 - SG360

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

| | | <u>, </u> | | Apr2024 | | |
|---------------|--------|--|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | UDI06147452 | | |
| Sample Date | | Client Info | | 09 Apr 2024 | | |
| Machine Age | hrs | Client Info | | 40547 | | |
| Oil Age | hrs | Client Info | | 10100 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.05 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | | |
| Nickel | ppm | ASTM D5185m | >3 | 0 | | |
| Titanium | ppm | ASTM D5185m | >3 | 0 | | |
| Silver | ppm | ASTM D5185m | >2 | 0 | | |
| Aluminum | ppm | ASTM D5185m | >10 | 0 | | |
| Lead | ppm | ASTM D5185m | >10 | 0 | | |
| Copper | ppm | ASTM D5185m | >50 | <1 | | |
| Tin | ppm | ASTM D5185m | >10 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | 90 | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | 90 | 52 | | |
| Calcium | ppm | ASTM D5185m | 2 | 0 | | |
| Phosphorus | ppm | ASTM D5185m | | 5 | | |
| Zinc | ppm | ASTM D5185m | | 7 | | |
| Sulfur | ppm | ASTM D5185m | | 21181 | | |
| CONTAMINANTS | 5 | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 0 | | |
| Sodium | ppm | ASTM D5185m | | 12 | | |
| Potassium | ppm | ASTM D5185m | >20 | 3 | | |
| FLUID DEGRADA | NOITA | method | limit/base | current | history1 | history2 |
| | | | | | | |


Acid Number (AN)

mg KOH/g ASTM D8045 0.4

0.46



OIL ANALYSIS REPORT




| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|-----------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | LIGHT | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPERT | TIES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D445 | 46 | 44.6 | | |


| Color | no im. | age no image |
|--------|--------|--------------|
| Bottom | no im. | age no image |

SAMPLE IMAGES



| 10 T :- | | | - | - | et | _ | - | | | | | | | | | | | | | | | | | |
|---------|-----------|-----|---|---|----|---|---|---|---|---|---|-------|---|---|---|---|---|---|---|---|--|---|---|---------|
| 8- | cop | per | - | | | | | | | | | | | | | | | | | | | | | |
| 6 | ⊶ tin | | J | | | | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | | | | - | - | - | | - | - | _ | - | _ | - | - | - | - | _ | - | - | - | | - | _ | - |
| Apr9/24 | | | | | | | | | | | | | | | | | | | _ | | | | | Apr9/24 |









Certificate 12367

Laboratory

Sample No. : UDI06147452 Lab Number : 06147452 Unique Number : 10977530

Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Tested

: 12 Apr 2024 : 15 Apr 2024 Diagnosed : 16 Apr 2024 - Sean Felton

DELTA INDUSTRIES - DOWNERS GROVE

2201 CURTISS STREET DOWNERS GROVE, IL US 60515

Contact: MICHAEL FERRIS

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (630)960-3931